

Technical Data Sheet

30mm Channelling Chisel

MATERIAL RECOMMENDATIONS

Heavy Duty Concrete	<input type="checkbox"/>	<input checked="" type="radio"/> Very suitable
General Concrete	<input type="checkbox"/>	<input checked="" type="radio"/> Very suitable
Hard Bricks	<input type="checkbox"/>	<input type="checkbox"/> Not suitable
Soft Bricks	<input checked="" type="radio"/>	
Lightweight Blocks	<input checked="" type="radio"/>	
Natural Stone	<input checked="" type="radio"/>	
Constructional Granite	<input type="checkbox"/>	
Limestone	<input type="checkbox"/>	
Mortar	<input type="checkbox"/>	



USAGE INFORMATION

- For use in tile, plaster, render removal applications.
- Prior to using chisels, please ensure your machine has the 'chisel only' function as they are designed to be used on this function only.
- Before using this product the chuck shank should be thoroughly lubricated.
- Minimal force should be applied when being used.
- After using the product continuously for 10-15 minutes the chisel must be removed from the chuck and allowed to cool at room temperature.
- Lubrication must be re-applied before re-using.
- Products can fail on the shank due to temperature build up of 200°C.
- Misuse of the product will decrease the maximum time usage significantly. Shank failure due to temperature build up is not warranted.

