CATALOGUE RANGE: FLUORESCENT



IP65 WEATHERPROOF FITTINGS

- 18W requires 1 or 2 x suitable 18W G13 T8 600mm fluorescent tubes (not included). Fitting is rated at 18W max (per lampholder)
- 36W requires 1 or 2 x suitable 36W G13 T8 1200mm fluorescent tubes (not included). Fitting is rated at 36W max (per lampholder)
- 58W requires 1 or 2 x suitable 58W G13 T8 1500mm fluorescent tubes (not included). Fitting is rated at 58W max (per lampholder)
- 70W requires 1 or 2 x suitable 70W G13 T8 1800mm fluorescent tubes (not included). Fitting is rated at 70W max (per lampholder)
- This luminaire is compatible with bulbs of the energy classes: A⁺⁺ to E
- Available as a single or twin fitting
- ABS base
- Polycarbonate diffuser: impact resistant
- Multiple fixing/suspension options
- Knockout and IP gland supplied for connections and through wiring
- Gear tray retaining strap: easy installation and maintenance
- High frequency ballast: instant start, flicker free operation and prolonged lamp life

EMERGENCY VERSIONS:

- 3 hour duration maintained operation • Emergency mode operates on one tube
- of twin fitting only
- WPFCLIP stainless steel clip amounts: **18W** = 6 clips / **36W** = 10 clips **58W** = 12 clips / **70W** = 14 clips
- 18W = M.O.M: 1 / O.P.O: 10

Code

WPF158EM3

WPF258EM3

WPF118

WPF218

WPF136

WPF236

WPF158

WPF258

WPF170

WPF270

WPFCLIP

- 36W / 58W / 70W = M.O.M: 1 / O.P.Q: 6
- WPFCLIP = M.O.M: 2 / O.P.Q: 500

Version

Single Emergency

Twin Emergency

Single

Twin

Single

Twin

Single

Twin

Single

Twin

Clip

R 18W: 675mm Single: 36W: 1278mm 88mm 58W: 1565mm Twin: 70W: 1855mm 132mm

Colour

Grey

Grey

Grey

Grev

Grey

Grey

Grey

Grey

Grey

Grey

Stainless Steel

Wattage

1 x 58W

2 x 58W

1 x 18W

2 x 18W

1 x 36W

2 x 36W

1 x 58W

2 x 58W

1 x 70W

2 x 70W

-

IP Rating

IP65

-



Standard

diffuser

included

clips

Suitable G13 T8

lamps available

See T8 EBRITE range





Stainless steel clips available

