




ATOM LED BULKHEAD

Highly cost effective, compact, ultra low energy, modern design utility bulkhead.



- Instant start to full illumination level: giving crisp, super bright light output (4200K)
- Polycarbonate construction: impact and corrosion resistant
- External fixing points: for quick & easy installation
- 3 x 20mm cable entries: offering multiple installation options
- Compact design

• M.O.M: 1 / O.P.Q: 20

Code	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
ATOM5	White	6W	4200K	450 lm	25,000 hrs	IP65	A+



Eterna ATOM5



The lamps cannot be changed in the luminaire.

874/2012

LED LAMP SPECIFICATIONS:	
Lumens total flux	450 lm
Lumens 120° flux	405 lm
Rated Wattage	6W
Rated luminous flux	450 lm
Nominal life time of the lamp	25,000 hrs
Colour temperature	4200K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
Lamp dimensions (L/W)	110 x 42mm
Nominal beam angle	120°
Rated power	6W
Rated lamp lifetime	25,000 hrs
Lamp power factor	>0.5
Lumen maintenance factor at end of nominal life	≥0.70
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	160cd
Rated beam angle	120°
Voltage	240V
Not suitable for accent lighting	