



This luminaire contains built-in LED lamps.



LED

The lamps cannot be changed in the luminaire.

874/2012



LED LAMP SPECIFICATIONS:

Lumens total flux	800 lm
Lumens 120° flux	730 lm
Rated Wattage	12W
Rated luminous flux	730 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	3100K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
Lamp dimensions (Ø)	140mm
Nominal beam angle	120°
Rated power	12W
Rated lamp lifetime	30,000 hrs
Lamp power factor	>0.93
Lumen maintenance factor at end of nominal life	≥0.70%
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within a 6 step Macadam ellipse
Rated peak intensity	480cd
Rated beam angle	120°
Voltage	200-240V


Not suitable for accent lighting

12W IP44 LED CEILING/WALL LIGHT

This stylish fitting is ideal for installation in a multitude of situations. Ceiling or wall mounted in a domestic or commercial setting and suitable for bathrooms. Long life, energy efficient alternative to traditional fluorescent luminaires.

- Multiple low power LED array & optically optimised diffuser: ensures a soft, even lighting effect with no degradation of light output
- Corrosion resistant stainless steel fixing screws
- Suitable for bathroom use
- 3100K warm colour temperature: offering a pleasing light appearance

• M.O.M: 1 / O.P.Q: 5



Code	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
PACIFIC12	Polished Chrome	12W	3100K	800 lm	30,000 hrs	IP44	A