



**COLLINGWOOD
LIGHTING**

FEATURES & BENEFITS

- › Can be easily cut on site with cut points every 100mm. Use in conjunction with LSF8, LSFCS8 and LSFCD8 connectors
- › 5m reels supplied in branded packaging
- › Ideal for short lengths up to 5m
- › Foil backed flexible PCB dissipates heat (improves LED life and colour stability)
- › 3M self-adhesive backing
- › NB: Cutting to required length will render this product non-returnable

LSV03

Constant voltage, self-adhesive, flexible IP20 strip



Bespoke length cutting service available



Ideal for use indoors



3-year guarantee



PHOTOMETRICS @ 25°C

Colour	Beam angle	CRI	lm/m	lm/W	lx @ 1m
4000K	150°	>80Ra	450	94	126
3000K	150°	>80Ra	450	94	126
2700K	150°	>80Ra	450	94	126

REEL ORDER CODES

LSV0340050 5m reel of 4000K LSV03 strip

LSV0330050 5m reel of 3000K LSV03 strip

LSV0327050 5m reel of 2700K LSV03 strip

For bespoke length, 050 to be replaced by required length. eg. 010 = 1m, 021 = 2.1m, etc
Part code calculator available at collingwoodlighting.com

GENERAL

Construction material Flexible tape

WIRING

Cable / flying lead Supplied with 250mm flying lead from one end


Type of wiring required Parallel

LED DRIVERS

Product code	mA	SELV	Dimming	Bathroom zone	Max (m)
PS3024	-	Yes	Yes (PDCINT1-10V)	-	5m
PSDIP6024	-	Yes	Yes	-	2 x 5m
PSDIP10024	-	Yes	Yes	-	4 x 5m

ACCESSORIES

Product code	Description
LSFC8 / LSFCS8 / LSFCD8	Range of fast fix connectors for use with LSV03
LED STRIP PROFILE RANGE	Profile range to house adhesive strip
LED COVE PACK	Coving to house adhesive strip
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers



4000K 150°

Additional diagrams available at collingwoodlighting.com

5m (cut point every 100mm)

