



This luminaire contains built-in LED lamps.

A++

A+

A

B

C

D

E

LED

The lamps cannot be changed in the luminaire.

874/2012



LED LAMP SPECIFICATIONS:

Lumens total flux	2000 lm
Rated Wattage	30W
Rated luminous flux	2000 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	4200K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
LED array dimensions (W/H)	198 x 167mm
Nominal beam angle	120°
Rated power	30W
Rated lamp lifetime	30,000 hrs
Lamp power factor	>0.9
Lumen maintenance factor at end of nominal life	≥0.70
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	720cd
Rated beam angle	120°
Voltage	220/240V


Not suitable for accent lighting



30W INTEGRATED LED BULKHEAD


- Captive stainless steel screws
- 20mm knockouts side and rear
- **WPACKLEDPC**: photocell for dusk to dawn operation

• M.O.M: 1 / O.P.Q: 4



Code	Version	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
WPACKLED	Standard	Black	30W	4200K	2000 lm	30,000 hrs	IP65	A
WPACKLEDPC	Photocell	Black	30W	4200K	2000 lm	30,000 hrs	IP65	A

Download IES File from website



Photocell



20mm knockouts



Captive stainless steel screws