

### Description

Novara Mains Voltage LED Strip 10M



### General

|                   |                               |
|-------------------|-------------------------------|
| Colour Options    | Clear Silicone Flexible Strip |
| Light Source      | Non-Replaceable LED Module    |
| LED Expected Life | 25,000 Hours                  |
| Product Warranty  | 2 Years from Date of Purchase |
| Mounting Method   | Floor, Wall or Ceiling Mount  |
| EAN               | 5060499510690                 |

### Electrical Parameters

|                  |                                      |
|------------------|--------------------------------------|
| Supply Voltage   | 220-240v AC                          |
| Frequency        | 50Hz                                 |
| Circuit Wattage  | 8.6W Per Metre (Total 86W)           |
| Circuit Current  | 0.04 Amps Per Metre (Total 0.4 Amps) |
| Driver mA Rating | N/A                                  |
| PFC              | 0.99                                 |
| In Rush Current  | N/A                                  |

### Classifications and Approvals

|                           |                             |
|---------------------------|-----------------------------|
| Earth Class               | Class II, No Earth Required |
| IP Rating                 | IP65                        |
| Efficiency Rated (Part L) | Yes Part L Compliant        |
| Energy Rating             | A+                          |
| CE Marked                 | Yes                         |
| Designed In Accordance to | BSEN60598                   |

### Installation

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| Mounting Bracket      | Supplied with 3 x "U" Clips per Metre              |
| Cable Entry           | N/A                                                |
| Method of Fix         | Screw Fix "U" Clips to Suitable Surface            |
| Working Ambient Temp. | -10°C to +45°C                                     |
| Primary Connections   | Plug & Play Connection                             |
| Secondary Connections | Plug & Play Connection                             |
| Max Linked Length     | 30 Metres Max                                      |
| Cutting Points        | N/A Cannot be Cut                                  |
| Accessories           | Additional Fixing Clips Available KSR9784, KSR9786 |

### Performance

|                          |                                          |
|--------------------------|------------------------------------------|
| Luminous Flux            | 580 Lumens Per Metre (Total 5800 Lumens) |
| Luminous Efficacy (L/pw) | 67 L/pw                                  |
| CCT                      | 6000k Cool White                         |
| CRI (Ra)                 | CRI Ra:80                                |
| Beam Angle               | 120°                                     |
| Dimmable                 | No, Non-Dimmable                         |
| Tilt/Rotate              | No, Fixed Position                       |

### Construction

|                  |                  |
|------------------|------------------|
| Main Chassis     | Flexible LED PCB |
| Trim/Bezel       | N/A              |
| Diffuser         | Clear Silicone   |
| Lens             | N/A              |
| Heat Sink        | N/A              |
| Finish Type      | Clear Silicone   |
| Luminaire Weight |                  |

