DESPHE Panel Heater





| Technical Details | | | | | | | |
|-------------------------|---|--|--|--|--|--|--|
| Controls | Digitally controlled, Electronic Thermostat accurate to (±0.2°C) Timer modes: 7 Day Programmable User Timer Continuous heat modes: Manual, Frost Protect, Off | | | | | | |
| Controller UI | Icon-based display with white backlight Capacitive buttons with audio feedback User replaceable battery (Coin-Type) | | | | | | |
| Controller Functions | Adaptive-start Advance time period Open Window Detection, Adaptive Start Adjustable max SP range (7-32°C) Bluetooth for software updates | | | | | | |
| Construction | •Durable epoxy-polyester powder coated steel casing with louvered forward facing grille •Advanced controls with cap-sense technology for total flexibility of heating | | | | | | |
| Element | Compact, finned, mineral filled sheathed element | | | | | | |
| Installation | 1 H-frame wall bracket for easy fixing | | | | | | |
| Safety | •Thermal cut-out. Auto reset type •Overheat detection | | | | | | |
| IP Rating | IP24 | | | | | | |
| Battery Backup | 3.3V coin cell battery to backup real time clock. Battery life > 5 years. | | | | | | |
| Supply | 1.3 metres fitted, 3 core for fused spur installation, 1/N/PE ~230-240 V, 50Hz Class I, with earth wire | | | | | | |
| Colour / Finish | Metal Chassis, Air Outlet Grille & Control Moulding - Traffic White (RAL 9016) | | | | | | |

| Warranty & Approvals | | | | | | |
|----------------------|----------------|--|--|--|--|--|
| Approvals | CE, BEAB | | | | | |
| Warranty | 1 years | | | | | |
| Country of Origin | United Kingdom | | | | | |
| Manufacturer | Denmans | | | | | |


Product Description

DESPHE features digital user controls, allowing the programming of 7-day timer profile via an icon-based display and capacitive buttons.

Key Features

- Intuitive user controls with icon-based display
- User programmable room temperatures with seven-day timer profile
- Electronic thermostat accurate to within 0.2°C
- Energy-saving technologies such as Adaptive Start and Frost Protect
- Slimline design that covers traditional panel heater fixing marks
- Forward facing slotted grille
- Splash-proof for use in bathrooms
- Complies with Lot 20 of ERP Directive

Dimensions



| | | | | | | | | 130 | 150 MIIN | | | |
|--|--------|-----------|--------|-----------|--------|-----------|--------|-----------|----------|-----------|--|--|
| Model/Item No.(EAN- Code 5011139+Item No.) | 090669 | DESPH075E | 090638 | DESPH125E | 090645 | DESPH150E | 090652 | DESPH200E | 090843 | DESPH300E | | |
| Output (kW) | 0.75 | | 1.25 | | 1.50 | | 2.00 | | 3.00 | | | |
| Height (mm) | 430 | | 430 | | 430 | | 430 | | 430 | | | |
| Width A (mm) | 620 | | 690 | | 690 | | 860 | | 860 | | | |
| Depth B (mm) | 108 | | 108 | | 1 | 108 | | 108 | | 143 | | |
| Weight (Kg) | 5.9 | | 6.1 | | 6.1 | | 7.8 | | 8.7 | | | |
| Packaging Details | | | | | | | | | | | | |
| Height (mm) | 470 | | 470 | | 470 | | 470 | | 470 | | | |
| Width (mm) | 660 | | 720 | | 720 | | 890 | | 890 | | | |
| Depth (mm) | 135 | | 135 | | 135 | | 135 | | 160 | | | |
| Packed Weight (Kg) | 6.5 | | 6.7 | | 6.7 | | 8.4 | | 9.8 | | | |
| Ti | 12 | | 10 | | 10 | | 9 | | 7 | 7 | | |
| Hi | 4 | | 4 | | 4 | | 4 | | 4 | 4 | | |
| Pallet Quantity (2.4m high) | 48 | | 40 | | 40 | | 36 | | 28 | | | |