

Conductor cross-section: 0.25 mm²

[illegible]

Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.
------	---

Inputs/outputs	2 x 8 analog inputs; current
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Rockwell	
Rockwell Control Logix	1756 - I/F16

Cable type	LiYCY
Color code	per DIN VDE 47100

Connector	D-subminiature female connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm ²

Connector 2	D-subminiature female connector
Pole number 2	25
Connection type 2	System

Connector 3	Allen Bradley 1756-TBS6H/A
Pole number 3	36
Connection type 3	System



Physical data		
Cable length		3 m

Material data		
Fire load		0 MJ
Weight		773 g

Environmental requirements		
Ambient temperature (operation)		-20 ... +50 °C

Commercial data		
Product Group		30 (WAGO France)
ETIM 8.0		EC000237
ETIM 7.0		EC000237
PU (SPU)		1 pcs
Country of origin		FR
GTIN		4050821356295
Customs tariff number		85444290900

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Downloads		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 706-4756/406-300		

Documentation		
System Description		
WAGO System Wiring, Selection Guide	pdf 533.15 KB	