

Conductor cross-section: 0.25 mm²



Societate		Societate		Societate	
Numar de inregistrare	Adresa	Numar de inregistrare	Adresa	Numar de inregistrare	Adresa
1	Str. 1 No. 1	2	Str. 2 No. 2	3	Str. 3 No. 3
4	Str. 4 No. 4	5	Str. 5 No. 5	6	Str. 6 No. 6
7	Str. 7 No. 7	8	Str. 8 No. 8	9	Str. 9 No. 9
10	Str. 10 No. 10	11	Str. 11 No. 11	12	Str. 12 No. 12
13	Str. 13 No. 13	14	Str. 14 No. 14	15	Str. 15 No. 15
16	Str. 16 No. 16	17	Str. 17 No. 17	18	Str. 18 No. 18
19	Str. 19 No. 19	20	Str. 20 No. 20	21	Str. 21 No. 21
22	Str. 22 No. 22	23	Str. 23 No. 23	24	Str. 24 No. 24
25	Str. 25 No. 25	26	Str. 26 No. 26	27	Str. 27 No. 27
28	Str. 28 No. 28	29	Str. 29 No. 29	30	Str. 30 No. 30
31	Str. 31 No. 31	32	Str. 32 No. 32	33	Str. 33 No. 33
34	Str. 34 No. 34	35	Str. 35 No. 35	36	Str. 36 No. 36
37	Str. 37 No. 37	38	Str. 38 No. 38	39	Str. 39 No. 39
40	Str. 40 No. 40	41	Str. 41 No. 41	42	Str. 42 No. 42
43	Str. 43 No. 43	44	Str. 44 No. 44	45	Str. 45 No. 45
46	Str. 46 No. 46	47	Str. 47 No. 47	48	Str. 48 No. 48
49	Str. 49 No. 49	50	Str. 50 No. 50	51	Str. 51 No. 51
52	Str. 52 No. 52	53	Str. 53 No. 53	54	Str. 54 No. 54
55	Str. 55 No. 55	56	Str. 56 No. 56	57	Str. 57 No. 57
58	Str. 58 No. 58	59	Str. 59 No. 59	60	Str. 60 No. 60
61	Str. 61 No. 61	62	Str. 62 No. 62	63	Str. 63 No. 63
64	Str. 64 No. 64	65	Str. 65 No. 65	66	Str. 66 No. 66
67	Str. 67 No. 67	68	Str. 68 No. 68	69	Str. 69 No. 69
70	Str. 70 No. 70	71	Str. 71 No. 71	72	Str. 72 No. 72
73	Str. 73 No. 73	74	Str. 74 No. 74	75	Str. 75 No. 75
76	Str. 76 No. 76	77	Str. 77 No. 77	78	Str. 78 No. 78
79	Str. 79 No. 79	80	Str. 80 No. 80	81	Str. 81 No. 81
82	Str. 82 No. 82	83	Str. 83 No. 83	84	Str. 84 No. 84
85	Str. 85 No. 85	86	Str. 86 No. 86	87	Str. 87 No. 87
88	Str. 88 No. 88	89	Str. 89 No. 89	90	Str. 90 No. 90
91	Str. 91 No. 91	92	Str. 92 No. 92	93	Str. 93 No. 93
94	Str. 94 No. 94	95	Str. 95 No. 95	96	Str. 96 No. 96
97	Str. 97 No. 97	98	Str. 98 No. 98	99	Str. 99 No. 99
100	Str. 100 No. 100	101	Str. 101 No. 101	102	Str. 102 No. 102
103	Str. 103 No. 103	104	Str. 104 No. 104	105	Str. 105 No. 105
106	Str. 106 No. 106	107	Str. 107 No. 107	108	Str. 108 No. 108
109	Str. 109 No. 109	110	Str. 110 No. 110	111	Str. 111 No. 111
112	Str. 112 No. 112	113	Str. 113 No. 113	114	Str. 114 No. 114
115	Str. 115 No. 115	116	Str. 116 No. 116	117	Str. 117 No. 117
118	Str. 118 No. 118	119	Str. 119 No. 119	120	Str. 120 No. 120
121	Str. 121 No. 121	122	Str. 122 No. 122	123	Str. 123 No. 123
124	Str. 124 No. 124	125	Str. 125 No. 125	126	Str. 126 No. 126
127	Str. 127 No. 127	128	Str. 128 No. 128	129	Str. 129 No. 129
130	Str. 130 No. 130	131	Str. 131 No. 131	132	Str. 132 No. 132
133	Str. 133 No. 133	134	Str. 134 No. 134	135	Str. 135 No. 135
136	Str. 136 No. 136	137	Str. 137 No. 137	138	Str. 138 No. 138
139	Str. 139 No. 139	140	Str. 140 No. 140	141	Str. 141 No. 141
142	Str. 142 No. 142	143	Str. 143 No. 143	144	Str. 144 No. 144
145	Str. 145 No. 145	146	Str. 146 No. 146	147	

Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.
------	---

Inputs/outputs	2 x 8 analog inputs; current
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Rockwell	
Rockwell Control Logix	1756 - I/F16

Cable type	LiYCY
Color code	per DIN VDE 47100

Connector	D-subminiature female connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm ²

Connector 2	D-subminiature female connector
Pole number 2	25
Connection type 2	System

Connector 3	Allen Bradley 1756-TBS6H/A
Pole number 3	36
Connection type 3	System



Physical data		
Cable length		2 m

Material data		
Fire load		0 MJ
Weight		999 g

Environmental requirements		
Ambient temperature (operation)		-20 ... +50 °C

Commercial data		
ETIM 8.0		EC000237
ETIM 7.0		EC000237
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		FR
GTIN		4055143119177
Customs tariff number		85444290900

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Downloads		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 706-4756/406-200		

Documentation		
System Description		
WAGO System Wiring, Selection Guide	pdf 533.15 KB	