


| | |
|---|---|
| product type designation | Plug-in cable RS232, D-sub-D /USB-A / PicoBlade |
| product description | flexible communication line SIMATIC RF1000 RS232 plug-in cable for RF1000 reader to PC with D-sub 9-pin plug, 5 V via USB A plug, length 1.8 m consisting of 6GT2891-7UA18, 6GT2091-7UH10. |
| suitability for use | Plug-in cable for connecting an RF1000 reader to a PC or other serial modules with submin D connection |
| wire length | 1.8 m |
| electrical data | |
| number of electrical connections | 3 |
| type of electrical connection | submin-D (female, 9-pole, straight) / USB-A / PicoBlade 51021 5-pole |
| mechanical data | |
| number of electrical cores | 5 |
| outer diameter | |
| • of cable sheath | 5 mm |
| standards, specifications, approvals | |
| reference code | |
| • according to IEC 81346-2 | WG |
| • according to IEC 81346-2:2019 | WGB |
| further information / internet links | |
| internet link | |
| • to web page: selection aid TIA Selection Tool | https://support.industry.siemens.com/cs/ww/en/view/67384964 |
| • to website: Industrial communication | http://www.siemens.com/ident/rfid |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAX-Download-Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| last modified: | 2/9/2022  |