

TOPFLEX®-EMV-2YSLCY-J

double screened, EMC-preferred type



TECHNICAL DATA

Motor connection cable for frequency converters in alignment with DIN VDE 0250

Temperature range	flexible +5°C to +70°C fixed -40°C to +70°C
Nominal voltage	AC U_0/U 600/1000 V
max. permissible operating voltage	alternating current (AC) conductor/earth 700 V three-phase alternating current (AC) conductor/conductor 1200 V direct current (DC) conductor/earth 900 V direct current (DC) conductor/conductor 1800 V
Test voltage core/core	4000 V
Mutual capacitance	see table
Coupling resistance	see table
Minimum bending radius	flexible < 12 mm: 10x Outer- \varnothing flexible > 12 mm: 15x Outer- \varnothing fixed 4x Outer- \varnothing

CABLE STRUCTURE

- Copper wire bare, finely stranded acc. to DIN VDE 0295 class 5 / IEC 60228 class 5
- Core insulation: PE
- Core identification: brown, black, grey, green-yellow
- G = with protective conductor GN-YE
- Cores stranded with optimal lay lengths
- 1. Screen: plastic-coated Aluminium foil (St)
- 2. Screen: braided screen of tinned copper, approx. coverage 85%

- Outer sheath: Special-PVC
- Sheath colour: transparent
- Length marking: in metres

PROPERTIES

- the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- optimal screening enables interference-free operation of frequency converters
- low coupling resistance ensures good electromagnetic compatibility
- low mutual capacitance of the individual cores due to PE core insulation and low screen capacity, enable low-loss power transmission

TESTS

- flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2
- electromagnetic compatibility acc. to DIN VDE 0875-11 / DIN EN 55011

APPLICATION

Used as a connecting cable for medium mechanical stress with fixed installation and occasional free movement in dry, damp or wet rooms, however, not suitable for outdoor use. Used in automotive, food, packaging and chemical industries, as well as in the environmental technology sector. EMC= Electromagnetic Compatibility; in order to optimise EMC properties, we recommend a double-sided and all-round large contact area of the copper braiding.

NOTES

- the conductor is metrically (mm²) constructed, AWG numbers are approximated, and are for reference only

Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer \varnothing mm, approx.	Mutual capacitance core/core in pF/m, approx.	Mutual capacitance core/screen in pF/m, approx.	Coupling resistance at 30 MHz in Ohm/km	Current carrying capacity*	Cu-weight kg/km	Weight kg/km, approx.
22084	4 G 1.5	16	10.1	70	110		18	95.0	161.0
22085	4 G 2.5	14	11.9	80	130	210	26	150.0	241.0
22086	4 G 4	12	13.6	90	150	210	34	235.0	343.0
22087	4 G 6	10	15.3	90	150	150	44	320.0	458.0
22088	4 G 10	8	19.4	120	200	180	61	533.0	707.0
22089	4 G 16	6	22.4	120	210	190	82	789.0	1112.0
22090	4 G 25	4	26.7	140	230	95	108	1236.0	1540.0
22091	4 G 35	2	29.3	150	260	85	135	1662.0	1957.0
22092	4 G 50	1	34.1	190	320	40	168	2345.0	2676.0
22093	4 G 70	2/0	39.0	190	320	45	207	3196.0	3740.0
22094	4 G 95	3/0	44.0	250	410	50	250	4316.0	4921.0
22095	4 G 120	4/0	48.7	270	430		292	5435.0	6171.0
22096	4 G 150	300 kcmil	54.2	280	450		335	6394.0	7585.0
22097	4 G 185	350 kcmil	60.6	290	470		382	7639.0	9449.0

*) Current carrying capacity with 3 loaded cores in amperes for permanent operation up to 30°C ambient temperature. For deviating ambient temperatures, the conversion factors and specifications from DIN VDE 0298-4 apply.