

# JZ-604 TC TRAY CABLE

PVC power cable, open installation TC-ER, NFPA 79, 90°C, 600 V, meter marking



HELUKABEL JZ-604 TC-ER UL 1277 18AWG / 1 QMM 7C 600V MTW 90C DRY 75C WET SUN RES DIR BUR OIL RES I OIL RES II ORAWM STYLE 2587 CSA AWM I/II A/B 90C FT4 600V LL113926 CE

## Technical data

- PVC power cable acc. to UL Std.1277 TRAY CABLE
- **Multinorm**  
also conforms to the following standards:  
AWM-Style 2587 to UL Std.758 and CSA-Std. C22.2 No.210 I/II A/B
- **Temperature range**  
dry environment  
flexing -5°C to +90°C  
fixed installation -25°C to +90°C  
wet environment  
flexing -5°C to +75°C  
fixed installation -25°C to +75°C
- **Nominal voltage**  
UL 600 V
- **Test voltage**  
3000 V
- **Breakdown voltage**  
min. 6000 V
- **Minimum bending radius**  
flexing 7,5x cable Ø  
fixed installation 4x cable Ø

## Cable structure

- Bare copper conductor, fine wire acc. to DIN VDE 0295 cl.5 / IEC 60228 cl.5
- Core insulation of PVC class 12 B acc. to tab. 50.155 UL Std.1581, type TFF to UL Std.62 (AWG 20-AWG 16) type THHW to UL Std.83 (≥ AWG 14)
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay length
- Outer sheath of PVC acc. to UL Std.1277 tab.11.2
- Sheath colour: black (RAL 9005)
- With meter marking

## Properties

- UV resistant
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

## Tests

- Self-extinguishing and flame retardant acc. to CSA FT4
- UL OIL RES I OIL RES II
- Class 1 Div. 2 per NEC Art. 336, 392, 501

## Note

- G = with GN-YE conductor  
x = without GN-YE conductor (OZ)
- AWG sizes are approximate equivalent values. The actual cross section is in mm<sup>2</sup>.
- Screened analogue type:  
**JZ-604-FCY TC TRAY CABLE**  
**JZ-604-YCY TC TRAY CABLE**

## Application

USA NFPA 79 conformant flexible power cables up to 600 V, for all machinery in tool and plant construction, suitable for installation in dry, humid and damp environments, in the open and in pipes. For underground installation and for open, unprotected installation from the cable rack to machines and industrial plants.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
69661	2 x 1	18	8,0	19,2	91,0
69662	3 G 1	18	8,4	29,0	105,0
69663	4 G 1	18	9,2	39,0	126,0
69664	5 G 1	18	10,0	48,0	149,0
69665	7 G 1	18	11,7	67,0	198,0
69666	9 G 1	18	12,6	84,0	245,0
69667	10 G 1	18	13,9	96,0	255,0
69668	12 G 1	18	14,7	115,0	309,0
69669	18 G 1	18	17,1	173,0	433,0
69670	25 G 1	18	20,3	240,0	576,0
69671	34 G 1	18	23,7	326,0	794,0
69672	50 G 1	18	27,8	480,0	1081,0
69673	2 x 1,5	16	8,4	29,0	106,0
69674	3 G 1,5	16	8,8	43,0	123,0
69675	4 G 1,5	16	9,6	58,0	148,0
69676	5 G 1,5	16	10,5	72,0	178,0
69677	7 G 1,5	16	12,3	101,0	236,0
69678	8 G 1,5	16	13,3	115,0	248,0
69679	9 G 1,5	16	13,3	130,0	300,0
69680	10 G 1,5	16	14,9	144,0	313,0
69681	12 G 1,5	16	15,6	173,0	377,0
69682	16 G 1,5	16	17,2	230,0	478,0
69683	18 G 1,5	16	18,2	259,0	534,0
69684	25 G 1,5	16	22,7	360,0	772,0
69685	34 G 1,5	16	25,3	489,0	988,0
69686	41 G 1,5	16	27,0	590,0	1158,0
69687	50 G 1,5	16	29,4	720,0	1352,0
69688	61 G 1,5	16	33,2	878,0	1728,0

Part no.	No. cores x cross-sec. mm <sup>2</sup>	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
69689	2 x 2,5	14	9,4	48,0	140,0
69690	3 G 2,5	14	9,9	72,0	165,0
69691	4 G 2,5	14	10,8	96,0	203,0
69692	5 G 2,5	14	11,8	120,0	241,0
69693	7 G 2,5	14	14,7	168,0	350,0
69694	8 G 2,5	14	16,2	192,0	421,0
69695	9 G 2,5	14	16,8	216,0	455,0
69696	10 G 2,5	14	17,1	240,0	451,0
69697	12 G 2,5	14	17,7	288,0	531,0
69698	18 G 2,5	14	20,8	432,0	751,0
69699	25 G 2,5	14	25,8	600,0	1076,0
69700	3 G 4	12	11,0	115,0	220,0
69701	4 G 4	12	12,0	154,0	272,0
69702	5 G 4	12	13,2	192,0	328,0
69703	7 G 4	12	16,5	269,0	495,0
69704	9 G 4	12	19,1	346,0	636,0
69705	12 G 4	12	19,9	461,0	726,0
69706	18 G 4	12	24,1	691,0	1086,0
69707	3 G 6	10	12,5	173,0	290,0
69708	4 G 6	10	14,5	230,0	382,0
69709	5 G 6	10	15,8	288,0	470,0
69710	7 G 6	10	17,3	403,0	609,0
69711	3 G 10	8	17,2	288,0	544,0
69712	4 G 10	8	18,9	384,0	678,0
69713	5 G 10	8	20,8	480,0	817,0
69714	7 G 10	8	23,7	672,0	1110,0

Continuation ▶

# JZ-604 TC TRAY CABLE

PVC power cable, open installation TC-ER, NFPA 79,  
90°C, 600 V, meter marking



Part no.	No. cores x cross-sec. mm <sup>2</sup>	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
69715	3 G 16	6	21,0	461,0	823,0
69716	4 G 16	6	23,9	614,0	1041,0
69717	5 G 16	6	26,3	768,0	1317,0
69718	7 G 16	6	28,8	1075,0	1676,0
69719	3 G 25	4	24,9	720,0	1192,0
69720	4 G 25	4	27,4	960,0	1499,0
69721	5 G 25	4	30,3	1200,0	1846,0
69722	7 G 25	4	38,2	1680,0	2580,0
69723	3 G 35	2	27,1	1008,0	1536,0
69724	4 G 35	2	29,8	1344,0	1932,0
69725	5 G 35	2	33,0	1680,0	2386,0
69726	3 G 50	1	33,2	1440,0	2238,0
69727	4 G 50	1	36,7	1920,0	2844,0
69728	5 G 50	1	41,5	2400,0	3579,0

Part no.	No. cores x cross-sec. mm <sup>2</sup>	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
69729	3 G 70	2/0	37,6	2016,0	2969,0
69730	4 G 70	2/0	42,0	2688,0	3837,0
69731	5 G 70	2/0	48,4	3360,0	4882,0
69732	3 G 95	3/0	41,8	2736,0	3811,0
69733	4 G 95	3/0	47,0	3648,0	4921,0
69734	5 G 95	3/0	52,5	4560,0	6140,0
69735	3 G 120	4/0	46,0	3456,0	4821,0
69736	4 G 120	4/0	51,5	4608,0	6243,0
69737	5 G 120	4/0	56,5	5760,0	7599,0
59378	4 G 150	300 kcmil	59,1	5760,0	8050,0
59379	4 G 185	350 kcmil	67,1	7104,0	9250,0

Dimensions and specifications may be changed without prior notice. (RN01)