




Omschrijving: For cable entry and routing or for installation of a power distribution system. Fixed to the top of the enclosure by four M12 screws. Available in both 200 mm and 300 mm height. The enclosure roof plate CCR can be used to close the top. For lifting a 200 mm high MCU together with an enclosure a separate lifting kit MCUK is needed.

Zijwanden: MCUP Supplied as an accessory.

Materiaal: Frame in 1.75 mm steel plate, panels in 1.35 mm steel plate.

Afwerking: RAL 7035 structured powder coating.

Beschermingsklasse: IP 41.

Levering: 1 piece with front and back panels including mounting material (without roof plate).

Voor behuizing			
H	B	D	Item nr.
200	400	600	MCU2046R5
200	400	800	MCU2048R5
200	600	600	MCU2066R5
200	600	600	MCU2068R5
200	800	600	MCU2086R5
200	800	800	MCU2088R5
200	1000	600	MCU2106R5
200	1000	800	MCU2108R5
200	1200	600	MCU2126R5
200	1200	800	MCU2128R5
300	400	600	MCU3046R5
300	400	800	MCU3048R5
300	600	600	MCU3066R5
300	600	800	MCU3068R5
300	800	600	MCU3086R5
300	800	800	MCU3088R5
300	1000	600	MCU3106R5
300	1000	800	MCU3108R5
300	1200	600	MCU3126R5
300	1200	800	MCU3128R5

* Available for MCSL enclosures.