



OUR BRAND

Three different quotations were received for a stunning bar. An interior designer stuck to a drawing table, finally realized the perfect colour to put on the walls. Endless discussions were held about the right chairs. The interior of a store, restaurant or hotel has to be on point. The design of the establishment determines atmosphere and appearance. It is part of your brand. But what to do with the lighting? How do you incorporate this into your design, to contribute to perception and atmosphere? Have you ever really thought about this?

At Internova, we plan and design professional LED lighting. Our main focus is in the retail and hospitality industry. As producers of light, we are proud of our broad selection of lighting products. We advise a lighting strategy based on LED modules, lumens, lighting colour and focal points. All our fixtures are made in The Netherlands. During the past 24 years, we have been part of many big hospitality and retail projects. Projects in collaboration with wholesalers and lighting specialists.

Our functional lighting is not only easy on the eye, but is designed with a purpose. Lighting not only has to contribute to the atmosphere, but it is also a part of the branding, routing and conversions. It takes more than just a set of lights and track to make it work. Lighting is a specialty, which makes it a real profession. And therefore; Internova: professional lighting.

PROFESSIONAL LIGHTING since 1996











71





34. Luminosa

35. Linea 60/100

36. Powergear Track

40. Powergear 48V

41. Lentiggino

42. Tracklights 48v













45. Lucevaria System

46. Led panel NLO

47. Centro

47. Tondo

48. Giro DLM

49. Giro SLM













50. Cerchio L

51. Etna

51. Visione 360

52. Girevole

53. Occhio

54. Curva













55. Doblar

56. Rondio

56. Cerchio

57. Dolina frame(less)

58. Vittorio

59. Taleggio













60. Moon Retail

62. Quadro

62. Piazza

64. Moon frame(less)

66. Luna frame(less)

68. Star frame(less)



71. Nuvola



72. Star Surface



72. Cubo up/down



73. Salina



74. Snello



75. Lipari



75. Orizzonte



76. Roswell



77. Riva



77. Diamante



78. Alta



79. Lucevaria Pendant

INTERNOVA

















Utility

That's where you want to work!

The right lighting in a utility environment contributes to the well-being of the employees and creates a pleasant working environment. Our lighting planners can build beautiful 3D lighting concepts according to the latest NEN standards, for the perfect office environment.



Shops

Seductively illuminated!

If the layout of a shop changes, the lighting should always be easy to adjust. That is why Internova tracklights in combination with our flexible Powergear® track system are perfect to use in any shop. Understand the art of seduction by creating a great product presentation using Internova's FASHION spots!



Restaurant & Bar

Make things happen!

In restaurants and bars, good lighting is not only important to create the perfect atmosphere, but must also be functional. By using the right combination of functional and decorative lighting a space can be brought to life.



Showroom

Don't be that simple!

Light creates atmosphere, branding, conversion and routing. Good showroom lighting does not consist of a simple combination of spots and tracks. For the right lighting, a well-thought-out lighting plan is essential. Internova designs and realizes customized (3D)lighting plans.



Supermarket

The volume can be increased!

A common mistake is the use of flat line lighting in a supermarket, which means that there is no atmosphere and a bad appearance. By creating the perfect balance between general lighting and spot lighting, our lighting designers can provide the right atmosphere. Also consider applying special lighting for fresh food and cosmetics! This makes a visit to these stores a pleasant experience which contributes to the increase of sales volumes.



Fresh Food

That tastes like more, doesn't it?!

Where other LED food modules can cause food to perish (e.g. aging of fresh meat and fish) within a few hours, the Premium Food LED modules by Internova are suitable for lighting fresh food products without any issues. This is achieved by selecting the correct wavelength combinations within the LED chips, the correct amount of light is also very important. The fresh food is displayed in the best possible way: true-to-life colours and a tasteful look.

LIGHTING DEFINITIONS

In our product descriptions you will find a number of typical lighting definitions and symbols. We have summarized some of the most commonly used product features in accessible descriptions.

LUMEN - Output of luminous flux

The amount of light output generated by a lightsource. The higher the lumen output, the higher the amount of light.

CRI Ra - Colour rendering index

Indicates on a scale 0-100 how natural a light source can render true colours of illuminated objects and spaces. Natural daylight has a CRI of 100Ra.

CCT - Collerated Colour Temperature

CCT is measured in degrees Kelvin (K) and indicates the colour appearance of the light source. Artificial light is mostly rated between 2200K and 5700K. The higher the temperature, the cooler the light.

UGR - Unified Glare Rating

The UGR is the index that quantifies the discomfort glare. UGR is rated between 10 and 28 whereby 10 is very comfortable. Office lighting should always be lower than 19 (UGR <19)

LED MODULES



Basic lighting module available in CRI >80Ra and >90Ra in 2700K, 3000K, 4000K, and 5700K



Excellent quality of light and colour rendition, combined with high energy efficiency. Ideal for creating ambience, fresh whites and depth of colour in many retail environments. Premium White module available in CRI >80Ra and >90Ra in 3000K and 4000K. Premium Ambiance module available in CRI >90Ra in 2200K.



LED modules dedicated towards fresh food applications. Food WarmWhite Module: Enhances the appearance of fresh food, such as bread, fruit and vegetables. Food Premium Meat Module: Enhances the appearance of fresh meat. Fresh Fish Module: Enhances the appearance of fresh fish.



Dim-to-Warm is a technology that reduces a luminaire's colour temperature when being (phase) dimmed, from 3000K to 2200K. This makes our Dim-to-Warm fixtures ideal to use in domestic and hospitality projects.



Tunable White allows you to control the colour temperature of a fixture between 2500K and 7000K. Our Tunable White fixtures can be controlled using the user friendly Casambi app.

OPTIONS













TRIAC - A switch that is used to control power by phase cutting. When used in lighting applications, it's commonly referred to as Triac dimming.

DALI - Protocol of controlling the luminaire whereby a data signal can control each driver individually.

1-10V - the driver generates an analogue signal of 1V (minimum) to 10V maximum, which reaches the dimmer switch (potentiometer) which modulates it.





I.FORZA

PHILIPS LED SLM INSIDE

3-Phase tracklight with built-in LED driver and aluminium die-cast heatsink. Suitable for high lumenflux up to 4500lm. Powder coating finish. Glass standard included.

Lumen: 1100lm, 2000lm, 3000lm, 4500lm

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K

4000K, 5700K



Reflector

Led modules



























ULTIMO



Options



Colour









Led modules


: >90Ra

: 3000K





Compose your own light!



Lumen: 1100lm :>90Ra CRI CCT : 2700K







Colour







Led modules











METEORA-S

0



Compose your own light!

100

Compact aluminium 3-phase tracklight with powder coating finish. Available with decorative golden, black or white inner ring. Standard Triac dimmable, ideal to be used in hospitality and domestic projects. Also available in a Dim-to-Warm version.

Lumen: 600lm CRI :>90Ra

: 2700K, DTW (3000K - 2000K) CCT





Colour

Reflector

Led modules

















VARIARE

CAMBIA





Colour



Reflector

or .

Led modules

Options

Colour



Reflector



Led modules Options



Dimmable





405



LUNGO

PHILIPS **LED SLM INSIDE**

3-Phase tracklight with built-in LED driver and aluminium die-cast heatsink. Powder coating finish. Glass standard included.

Lumen: 1100lm, 2000lm, 3000lm

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Colour





Reflector











Led modules













Options







Ø 109

INTERNO

PHILIPS **LED SLM INSIDE**

Compact 3-Phase tracklight with built-in LED driver and aluminium die-cast heatsink. Powder coating finish. Glass standard included.

Lumen: 1100lm, 2000lm, 3000lm

:>80Ra,>90Ra CRI

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Colour



Reflector















Options

Led modules











Ø 85

012





BALENO

RGBWW + TW

Aluminium 3-phase tracklight, standard equipped with a Bluetooth Casambi receiver. This tracklight is available in a RGBWW and TW version, CRI>90. With this tracklight it is also possible to create a Human Centric Lighting environment. Also availbale in DALI version

CASAMBI

Lumen: 3000lm : >90Ra CRI

Available in:

- -RGBWW (RGBW + 2500-7000K)
- -TW (2500-7000K)

Casambi is a bluetooth low energy lighting solution. A large number of our fixtures can be equipped with the Casambi option. All Casambi products automatically form a wireless mesh network. It can be controlled by smartphones, tablets or smart watches. The Casambi App can be downloaded for free in the App store. With Casambi you can:

- · Dim the lighting*
- · Group luminaires and controll them together
- · Configure, save and recall scenes
- Adjust light colours*
- Adjust colour temperatures*
- Take pictures and add lighting control directly to your picture
- Defining timers for the purpose of Human Centric Lighting*
- * Fixtures have to be equiped with this feature









71

MERCATO

GALLERIA

PHILIPS LED SLM INSIDE

3-Phase tracklight with aluminium die-cast heatsink and driverbox. Powder coating finish.

Lumen: 1100lm, 2000lm, 3000lm

CRI: >80Ra, >90Ra

CCT: 2700K, 3000K, 4000K, 5700K

, 5700K

Colour







Reflector





Led modules





Options

PHILIPS LED SLM INSIDE

Compact 3-phase aluminium tracklight with passive cooling body and driverbox. Powder coating finish.

Lumen : 1100lm, 2000lm CRI : >80Ra, >90Ra

CCT: 2700K, 3000K, 4000K, 5700K



Colour

Reflector

20°

Reflector 30°

Led modules Options
Standard Dimma

ard Dimm





PRESENTA

PHILIPS LED SLM INSIDE

3-Phase aluminium tracklight with industrial look and seperate driverbox. Powder coating finish.

Lumen: 1100lm, 2000lm, 3000lm, 4500lm

CRI: >80Ra, >90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K



Colour



Reflector

15° 24°

40°

60°

• Standard

Led modules























FINESTRA

LED SLM INSIDE

3-Phase tracklight with aluminium die-cast heatsink and driverbox. Powder coating finish. Suitable for high lumenflux.

Lumen: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm

CRI :>80Ra,>90Ra

: 2200K, 2700K, 3000K, 4000K, 5700K CCT



Colour

Reflector





Led modules





















CONCENTRA

PHILIPS

LED SLM INSIDE

3-Phase aluminium tracklight with industrial look and seperate driverbox. Powder coating finish. Suitable for high lumenflux, up to 6000lm.

Lumen: 1100lm, 2000lm, 3000lm,

4500lm, 6000lm

CRI: >80Ra, >90Ra

CCT: 2200K, 2700K, 3000K, 4000K,

5700K



Colour

Reflector

. . .

ector



VELA

PHILIPS **LED SLM INSIDE**

3-Phase track Wallwasher with a very wide beamangle. Ideal for lighting wall presentations. Powder coating finish.

Lumen: 1100lm, 2000lm, 3000lm, 4500lm

CRI : >80Ra, >90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K





NLO TRACK



Aluminium 3-phase wallwasher equipped with unique Powergear® Ultimate Adapter with built-in LED driver. Darklight reflectors with low glare.

Lumen: 2600lm CRI :>80Ra.

CCT : 3000K, 4000K

UGR : <13



336

Colour

Reflector

Led modules

Options















Led modules





















DIABLO

PHILIPS LED SLM INSIDE

Aluminium 3-phase tracklight equipped with unique Powergear Ultimate Adapter® with built-in LED driver.

Lumen : 1100lm, 2000lm, 3000lm

CRI : >80Ra, >90Ra

CCT : 2700K, 3000K, 4000K, 5700K



Ø 80















Led modules























DIABLO-L

PHILIPS LED SLM INSIDE

Powerful aluminium 3-phase tracklight equipped with unique Powergear Ultimate Adapter® with built-in LED driver. Powder coating finish.

Lumen: 1100lm, 2000lm, 3000lm, 4500lm, 5500lm

CRI: >80Ra, >90Ra

CCT: 2700K, 3000K, 4000K, 5700K



Colour

Reflector

Led modules



























VELOCE



Aluminium 3-phase tracklight equipped with unique Powergear Ultimate Adapter® with built-in LED driver. Powder coating finish. Glass standard included.

Lumen: 1100lm, 2000lm, 3000lm, 4000lm

CRI: >80Ra, >90Ra

CCT: 2700K, 3000K, 4000K, 5700K



Colour



Reflector

15° 24

24°

Reflector

Standard

Led modules

Premium

um

Dimmable







TRIPOLORE

PHILIPS LED SLM INSIDE

Unique and compact 3-headed tracklight with a lumen-output up to 3x1500lm. Ideal to illuminate product displays in shops and supermarkets.

Lumen : 3x 800lm, 3x 1500lm

CRI :>80Ra,>90Ra

CCT : 2700K, 3000K, 4000K 5700K



Colour



Reflector









Led modules







PHILIPS LED SLM INSIDE

Compact aluminium 3-phase tracklight equipped with unique Powergear Ultimate Adapter® with built-in LED driver. Powder coating finish.

Lumen : 1100lm, 2000lm CRI : >80Ra, >90Ra

CCT : 2700K, 3000K, 4000K, 5700K



Colour

Reflector

Led modules

















TUBULO



Simple and sleek 3-phase track spot with GU10 lampholder. Suitable for GU10 LED spot. Powder coating finish.

Supplied without lightsource.

STRETTO

OSRAM

LED Inside

Compact 3-phase aluminium tracklight with passive cooling body and AC LED module. Powder coating finish.

Lumen : 1500lm CRI : >80Ra CCT : 3000K Ø 70

120

Colour



Colour













Colour Colour Colour





IL PODIO

PHILIPS LED SLM INSIDE

Theatre-look 3-phase tracklight with built-in LED driver and aluminium die-cast heatsink. Powder coating finish. Supplied including barndoors.

Lumen: 1100lm, 2000lm, 3000lm

CRI :>80Ra,>90Ra

: 2200K, 2700K, 3000K, 4000K, 5700K CCT



Colour

Reflector

Led modules









































Vintage 3-phase tracklight with G53 lampholder. Suitable for AR111 LED spot. Supplied including 350mA Triac dimmable LED driver.

Lightsource advice: Optiled Array AR111 927/DTW 800lm (as shown on the product picture).



Colou

Options







150

Ø 118



FUGA

OSRAM LED Inside



Compact track mounted emergency light. Easy and quick to install due to the incorporated 3-circuit track adapter.

- Non maintained
- Self-test
- Symmetrical lens

: 200lm Lumen CCT : 4000K

Autonomy : 1h emergency

Charge time : 24h

LABARRA

OSRAM LED Inside



Aluminium linear 3-phase tracklight with high lumen output. Powder coating finish. Ideal to be used in high space and warehouses.

Lumen: 4500lm, 6000lm, 14000lm

CRI :>80Ra

CCT : 3000K, 4000K





Colour



Reflector





Reflector



Led modules





1148




LUCEVARIA TRACK

OSRAM LED Inside

Linear LED profile (45x78mm) for 3-phase track with a opal diffusor.

590mm : 1500lm 1150mm : 3000lm 1430mm : 3850lm

CRI :>80Ra,>90Ra CCT : 3000K, 4000K



Colour



Led modules Reflector









LUMINOSA TRACK / SURFACE

OSRAMLED Inside


Linear light available in surface mounted and 3-phase track version. Can be equipped with a wide variety high efficiency lenses.

The surface mounted version van easily be installed due to the use of magnets. Through-wiring available upon request.

1140mm (only 4000K): 4500lm, 6000lm (only 4000K) 1700mm (only 4000K): 6000lm, 9000lm (only 4000K)

CRI: >80Ra, >90Ra

CCT: 3000K, 4000K, 5000K, 6500K



Colour

Reflector



Reflector 60°







Led modules









Linear LED fixture with a 3-phase track connection. Ideally suited for general lighting. Equipped with opal diffusor.

Lumen : 1500lm (Linea 60) / 2500lm (Linea 100)

CRI :>80Ra

CCT : 3000K, 4000K

Colour

Reflector

Led modules








POWERGEAR TRACK

POWERGEAR®

SURFACE MOUNTED 3-PHASE TRACK




High quality 3-Phase track for professional and flexible lighting solutions. PowerGear track is suitable for tracklights with 3-Phase adapter of all major brands! PowerGear is being produced under certified ISO9001 and ISO14000 regulations and it features ENEC, UL, TUV/GS labels.

Also available as recessed track, request our Powergear brochure for the full program.

















Colour





Coupler PRO-0433

End cap PRO-0432



Mounting clamp PRO-04SK



Suspension kit with 5m wire PRO-EZ0449

Adjustable T-connector Left

PRO-M436L

Middle Connector PRO-0434

Adjustable connector

PRO-M435

X-connector PRO-0437



Fixed monopoint 3-phase PRO-C100



3-Phase track adaptor

PRO-0222













Adjustable L-connector




Adjustable T-connector Right PRO-M436R

POWERGEAR®









DALI 1F Connector Left PRO-D431L



DALI 1F T-connector Left PRO-D436L1



DALI 1F Connector Right PRO-D431R



DALI 1F T-connector Left PRO-D436L2



Standard 3 phase track can be converted to DALI 1 phase track with accessories listed on this page.

Coupler and end cap are the same as used in standard 3 phase track (PRO-0433 en PRO-0432).

Also available as recessed track, request our Powergear brochure for the full program.



DALI 1F L-connector Left PRO-D435L



DALI 1F Middle Connector PRO-D434



DALI 1F L-connector Right PRO-D435R



DALI 1F Flexible Connector PRO-D439



DALI 1F T-connector Right PRO-D436R1



DALI 1F X-connector PRO-D437






DALI 1F T-connector Right PRO-D436R2



1-Phase DALI Track adaptor PRO-D480






3-PHASE DALI TRACK

1 meter PRO-0610 2 meter PRO-0620 3 meter PRO-0630

Also available as recessed track, request our Powergear brochure for the full program.







DALI Connector Right PRO-D631R



DALI Coupler PRO-D633



DALI T-connector Left PRO-D636L1



DALI T-connector Right PRO-D636R2



DALI T-connector Left PRO-D636L2

DALI Middle Connector

PRO-D634





DALI L-connector Right PRO-D635R



DALI Flexible Connector PRO-D639



DALI X-connector PRO-D637



DALI Track adaptor PRO-D680




DALI T-connector Right PRO-D636R1


POWERGEAR®

48V Low voltage track system

The high quality Powergear 48V lighting track system for the professional lighting market is suitable for tracklights with Powergear 48V adapters. Specially designed for high-end (domestic) market due to its slim and subtle look. A comprehensive range of innovative accessories and a multitude of different adapters, give designers maximum freedom to create unique and smart 48V lighting designs. Powergear 48V lighting track comes in various surface mounted and recessed versions. The "EZCLICK" mounting features complete the system and make the track system quick and easy to install.




SURFACE MOUNTED TRACK






SURFACE MOUNTED DEEP TRACK




Low Voltage Single Circuit DALI



Low Voltage 2 Circuits








Colour



Request our Powergear brochure for the full 48V program.



SALINA

Decorative pendant in powder coating finish. Available in black (golden inner ring) and white (black inner ring). Only compatible with the Powergear® 48V system. Ideal to be used in domestic and hospitality projects.

Lumen : 600lm CRI : >90Ra CCT : 2700K

Colour

400

Reflector










LENTIGGINI

Linear lighting for Powergear 48V. Low UGR due to dark-light reflector.

Lumen: 900lm CRI: >90Ra

CCT : 2700K, 3000K



219

Colour

Reflector




















22

BANDA

243

Lumen: 200lm CRL :>90Ra

CCT: : 2700K, 3000K



BANDA

Lumen: 400lm CRL :>90Ra CCT : 2700K, 3000

BANDA³

Lumen: 620lm CRL :>90Ra

CCT : 2700K, 3000K

Banda serie:

Linear light with opal diffusor for Powergear 48V track system. Ideal to be used for general lighting in combination with our Sotille spot light series.

Colour

Led modules Options









Colour

Led modules Options









22

LUCEVARIA SYSTEM

Design and multi-funtionality in one smart solution. To be used as pendant or surface mounted lighting. Linear lighting combined with spot lights for state of the art Lighting design. Powder coating finish.

Modular lighting system can be composed with following parts:

- Aluminium Profile (45x78mm) with a length of 1430mm, 1150mm or 590mm
- · Various accessories available, see next page
- Available with blind cover, opal diffusor and blind cover with spots.

Linear Lighting

 1430mm
 3850 lumen

 1150mm
 3000 lumen

 590mm
 1500 lumen

Specific lumen output upon request.

CCT : 3000K, 4000K CRI : >80Ra, >90Ra

OSRAM LED Inside

Spot Lighting



Lumen : 1100lm, 2000lm

CCT: 2700K, 3000K, 4000K

CRI: >80Ra, >90Ra



No Lighting (blind cover)

1430mm 1150mm 590mm



Colour









Led modules











LUCEVARIA MODULAR SYSTEM

Opal diffusor 1430mm, 1150mm, 590mm Blind cover 1430mm, 1150mm, 590mm Suspension kit 3m including 230V cable Suspension Kit 3m steel cable



Coupler







Corner 90°



T junction







LED PANEL NLO



Featuring New Louvre Optic technology. The NLO panel offers the ideal combination of stylish design and optimum performance for both task and general lighting. Low glare.

:>80Ra CRI

CCT : 3000K (3570lm), 4000K (3850lm)

UGR : <13

595

Colour

Options





595

CENTRO

PHILIPS **LED DLM INSIDE**

Economic IP44 LED downlight with Philips Fortimo LED DLM. Glass standard included. Powder coating finish.

: 1100lm, 2000lm, 3000lm, 4500lm Lumen

CRI :>80Ra

CCT : 3000K, 4000K Cut-out size : Ø200 x H128mm



Colour

Reflector

Led modules



Options









TONDO

PHILIPS **LED SLM INSIDE**

LED downlight with smooth reflector. Low glare. Powder coating finish.

: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm Lumen

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : Ø193 x H161mm

UGR : <16









Colour









































GIRO DLM 180/206/226



Economic LED downlight equipped with a Philips Downlight Module. Available in 3 sizes: 180mm, 206mm and 226mm. IP44 set with frontglass available upon request.


: 1100lm, 2000lm, 3000lm, 4500lm Lumen

CRI :>80Ra

CCT : 3000K, 4000K

Cut-out sizes : GIRO180 Ø170 x H130mm

GIRO206 Ø190 x H132mm GIRO226 Ø215 x H137mm



Colour



Reflector

Led modules













GIRO SLM 180/206/226

PHILIPS LED SLM INSIDE


Highly efficient LED downlight equipped with a Philips SLM Module. Available in 3 sizes: 180mm, 206mm and 226mm. IP44 set with frontglass available upon request.

: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm Lumen

CRI :>80Ra,>90Ra

CCT : 2700K, 3000K, 4000K, 5700K Cut-out sizes : GIRO180 Ø170 x H130mm

> GIRO206 Ø190 x H132mm GIRO226 Ø215 x H137mm





Colour

Reflector















Ø226



CERCHIO-L



Compact LED Downlight with a deep reflector. Low glare (UGR <13).

: 1100lm, 2000lm, 3000lm, 4500lm Lumen

CRI :>80Ra,>90Ra

CCT : 2700K, 3000K, 4000K, 5700K

Cut-out size : Ø155 x H160mm

UGR : <13



Colour



Reflector










Led modules























ETNA



Ø 120

VISIONE 8

Compact gimbal recessed fixture. Equipped with a unique 360° turnable system and 30° tiltable. Standard equipped with Dim-to-Warm LED Module and Triac dimmable driver.

: 520lm Lumen CRI : >90Ra

CCT : DTW 3000K - 1800K

Cut-out size : Ø76 x H50mm



Compact LED Downlight with a deep reflector. Powder coating finish. Glass standard included

: 1100lm, 2000lm, 3000lm Lumen

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

: Ø105 x H113mm Cut-out size



Colour





Reflector





















Options















Reflector



Led modules



Options



Colour



GIREVOLE



Gimbal recessed LED spot. Ideal for retailshops. Powder coating finish.

: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm Lumen

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : Ø170 x H110mm



Colour

















Led modules















Options













Ø 180





OCCHIO



Recessed LED wallwasher with a very wide beam angle. Ideal for lighting wall presentations. Powder coating finish. Glass standard included.

: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm Lumen

CRI : >80Ra, >90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : L220 x W122 x H90mm



Colour

Reflector

Led modules

















CURVA

PHILIPS LED SLM INSIDE

Curved recessed LED spot. Turnable and tiltable. Ideal for retailshops. Powder coating finish.

: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm Lumen

CRI : >80Ra, >90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : Ø162 x H141mm



Colour



Reflector









Led modules

































DOBLAR

PHILIPS LED SLM INSIDE

Compact curved recessed LED spot. Turnable and tiltable. Ideal for retail shops. Glass standard included. Powder coating finish.

: 1100lm, 2000lm, 3000lm Lumen

CRI : >80Ra, >90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : Ø130 x H114mm



Colour



























Led modules









RONDIO

PHILIPS LED SLM INSIDE



Ø 130

Round turn- and tiltable recessed LED spot. Glass standard included. Powder coating finish.

Lumen : 1100lm, 2000lm, 3000lm

CRI : >80Ra, >90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : Ø115 x H94mm

CERCHIO

PHILIPS LED SLM INSIDE




Ø 91


Fixed round recessed fixture with extra deep reflector and low glare. Standard Triac dimmable.

UGR : <15

Lumen : 800lm, 1400lm CRI : >80Ra, 90Ra

CCT : 2700:, 3000K, 4000K









DOLINA **FRAMELESS** PHILIPS



Ø 78

Tiltable recessed frameless fixture with deep reflector. 350° turnable and 30° tiltable. Standard Triac dimmable. Also available with golden inner ring.

: 800lm, 1400lm Lumen LED Modules: 830, 927, 940 Cut-out size : Ø100 x H97mm

LED SLM INSIDE

DOLINA

PHILIPS **LED SLM INSIDE**



Tiltable recessed fixture with deep reflector. 350° turnable and 30° tiltable. Standard Triac dimmable. Also available with golden inner ring.

: 800lm, 1400lm Lumen LED Modules: 830, 927, 940 Cut-out size : Ø90 x H97mm



Colour

Reflector

Led modules

Options





Colour





Reflector



Led modules







VITTORIO

PHILIPS LED SLM INSIDE

Economic square LED downlight equipped with a Philips Downlight Module.

: 1100lm, 2000lm, 3000lm Lumen

CRI : >80Ra

CCT : 3000K, 4000K

Cut-out size : 190 x 190 x H 134mm





Reflector

Led modules Options























TALEGGIO

PHILIPS LED SLM INSIDE


Square recessed LED spot with a deep reflector (low glare). Available with a black or gold inside. Standard Triac dimmable.

: 800lm, 1400lm Lumen CRI :>80Ra,>90Ra

CCT : 2700K, 3000K, 4000K

UGR : <13

Cut-out size : 98 x 98 x 124mm



Colour

Reflector

Led modules

Standard













MOON RETAIL



MOON I RETAIL

Single recessed gimbal LED spot. Cut-out size: L165 x W165 x H145mm

MOON II RETAIL

Double recessed gimbal LED spot. Cut-out size: L325 x W165 x H145mm

Lumen: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K





335

Colour



Reflector

Reflector









Led modules

































Triple recessed gimbal LED spot. Powder coating finish.

Lumen : 1100lm, 2000lm, 3000lm, 4500lm, 6000lm

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : L470 x W165 x H145mm



483

Colour

Reflector















































QUADRO

PHILIPS **LED SLM INSIDE**

Square turn- and tiltable recessed LED spot. Glass standard included. Powder coating finish.

: 1100lm, 2000lm, 3000lm Lumen

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K

Cut-out size : Ø115 x H94mm

PIAZZA

PHILIPS

LED SLM INSIDE

Fixed square recessed fixture with extra deep reflector and low glare. Standard Triac dimmable.

: 800lm, 1400lm Lumen CRI :>80Ra, 90Ra CCT : 2700:, 3000K,

4000KUGR : <13

Cut-out size : L86 x W86 x H118mm

Colour



Reflector



Reflector













Led modules

Options









Colour







Reflector



Led modules





MOON FRAME

Gimbal recessed spot with modern look. Tilt- and swivel rings. Suitable for domestic and hospitality applications. For shop lighting we recommend the Moon Retail.

MOON I FRAME

Single recessed spot. Cut-out size: L165 x W165 x H111mm

MOON II FRAME

Double recessed spot. Cut-out size: L350 x W165 x H111mm

Lamptype AR111 LED. Supplied without powersupply and lightsource, available upon request.







MOON FRAMELESS

Frameless gimbal recessed spot with modern look. Tilt- and swivel rings. Suitable for domestic and hospitality applications. Plasterframe included. For shop lighting we recommend the Moon Retail.


MOON I FRAMELESS

Single recessed spot. Cut-out size: L165 x W165 x H110mm

MOON II FRAMELESS

Double recessed spot. Cut-out size: L315 x W165 x H110mm

Lamptype AR111 LED. Supplied without powersupply and lightsource, available upon request.



Colour



LUNA FRAME

Gimbal recessed spot. Tilt- and swivel rings. Suitable for domestic and hospitality applications.

LUNA I

Single recessed spot. Cut-out size: L120 x W120 x H125mm

LUNA II

Double recessed spot. Cut-out size: L240 x W120 x H125mm

Lamptype AR70 LED. Supplied without powersupply and lightsource, available upon request.







LUNA FRAMELESS

Frameless gimbal recessed spot. Tilt- and swivel rings. Suitable for domestic and hospitality applications. Plasterframe included.


LUNA I FRAMELESS

Single recessed spot.
Cut-out size: L120 x W120 x H120mm

LUNA II FRAMELESS

Double recessed spot.
Cut-out size: L225 x W120 x H120mm

Lamptype AR70 LED. Supplied without powersupply and lightsource, available upon request.



Colour



STAR FRAME

Gimbal recessed spot. Tilt- and swivel rings. Suitable for domestic and hospitality applications.

STAR I

Single recessed spot. Cut-out size: L115 x W115 x H125mm

STAR II

Double recessed spot. Cut-out size: L210 x W115 x H125mm

Lamptype GU10 LED or 50mm LED module. Standard supplied without lightsource, available upon request.



132



132

237

Colour



STAR FRAMELESS

Frameless gimbal recessed spot. Tilt- and swivel rings. Suitable for domestic and hospitality applications. Plasterframe included.

STAR I FRAMELESS

Single recessed spot.

Cut-out size: L115 x W115 x H120mm

STAR II FRAMELESS

Double recessed spot.

Cut-out size: L215 x W115 x H120mm

Lamptype GU10 LED or 50mm LED module. Standard supplied without lightsource, available upon request.



210

Colour



5



NUVOLA ROUND SQUARE

Surface mounted spotlight with powder coating finish. Standard equipped with Dim-to-Warm LED module and Triac dimmable driver.

Lumen: 900lm CRI: >90Ra

CCT : 3000K - 1800K (DTW)





Colour







STAR SURFACE

Gimbal surface mounted spot. Tilt- and swivel rings. Suitable for domestic and hospitality applications.


STAR I SURFACE

Single surface mounted gimbal spot.

STAR II SURFACE

Double surface mounted gimbal spot.

Lamptype GU10 LED. Supplied without lightsource, available upon request.




CUBO UP/DOWN

Compact IP65 wall fixture, up/down. Standard triac dimmable. Beam angle can be adjusted manually (1°-120°).

Lumen : 2x 160lm CRI : >80Ra

CCT : 2700K, 3000K



Colour

Led modules

Standard














SALINA

Decorative pendant in powder coating finish. Available in black (golden inner ring) and white (black inner ring). Standard Triac dimmable. Suspension length. Also available in a 3-circuit track version.

Lumen : 600lm CRI : >90Ra CCT : 2700K

Colour



Reflector



Standard

Led modules



SNELLO

PHILIPS LED SLM INSIDE

Surface mounted tubular LED spot. Powder coating finish.

Lumen: 1100lm, 2000lm, 3000lm

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K



Ø 118



Led modules

Options







Reflector





















200

LIPARI

ORIZZONTE

PHILIPS LED DLM INSIDE

Surface mounted downlight with powder coating finish. Available in black (golden inner ring) and white (black inner ring). Standard Triac dimmable. Also available in a 3-circuit track version.

Lumen : 1500lm CRI : >90Ra CCT : 2700K



Economic surface mounted LED downlight with Philips Fortimo LED DLM. Powder coating finish.
Also available in a 3-circuit track version.

Lumen: 1100lm, 2000lm, 3000lm

CRI :>80Ra

CCT: 3000K, 4000K



Ø 245

Colour

Reflector

Le

Led modules Options

Reflector

ard

Dimmable











Colour





Reflector



Led modules













ROSWELL

PHILIPS

LED SLM INSIDE

Industrial crafted LED pendant in vintage black outside and matt white inside. Suspension length 2m.

Lumen: 1100lm, 2000lm, 3000lm

CRI :>80Ra,>90Ra

: 2200K, 2700K, 3000K, 4000K, 5700K CCT





Ø 500

Colour

Reflector

Led modules





























RIVA

Vintage crafted pendant in matt black and white inside. Equipped with an E27 socket and 3m black fabric wire.

Supplied without lightsource, available upon request.



Ø 350

DIAMANTE



Industrial-shaped pendant lamp with matt black finish and faceted, white inside. Suspension length 3m.

Lumen: 2000lm : >80Ra CRI CCT : 3000K



Colour



Reflector

Led modules Options









ALTA



LED Pendant in industrial look, produced in die-cast aluminium. Supplied with Ø410mm prismatic polycarbonate shade. Suspension length 3m.

Lumen: 1100lm, 2000lm, 3000lm, 4500lm, 6000lm

CRI :>80Ra,>90Ra

CCT : 2200K, 2700K, 3000K, 4000K, 5700K



Colour









Reflector











Led modules

















OSRAM LED Inside

Linear pendant lighting (59cm, 115cm or 143cm) for the perfect utility lighting. Ideal to be used for desk and counter lighting. Supplied including suspension kit, suspension length 3m.

590mm : 1500lm : 3000lm 1150mm 1430mm : 3850lm

CRI :>80Ra

CCT : 3000K, 4000K

Colour

Led modules Options

















#