Code: 420665-00

5




The Vega wall sconce, one of Disano's most popular wall lamps, combines excellent material quality and distinctive design with LED technology, which guarantees energy savings and long life. The unique shape of its housing allows for simple and functional installations. Also available with presence sensor to enhance functionality and service life.



		GENERAL INFORMATION	
Article	1264 - Vega LED		
Code	420665-00		
		DIMENSIONS AND WEIGHT	
Length (mm)	300 mm		
Width (mm)	225 mm		
Height (mm)	142 mm		
Weight (Kg)	1.500 kg		
		ELECTRICAL CHARACTERISTICS AND CONTROLS	
Voltage type	AC		
Min Voltage (V)	220 V		
Max Voltage (V)	240 V		
Min Frequency (Hz)	50 Hz		
Max Frequency (Hz)	60 Hz		
Frequency (Hz)	50 Hz		
Wiring name	CLD		
Power factor	≥0.9		
Insulation class	Class I		
Controllability	None		



#### Code: 420665-00



Lighting source	LED				
CRI	70				
Luminous flux (output) (lm)	1657 lm				
Power absorption (total) (W)	20 W				
ССТ	4000 K				
Luminous efficacy (Im/W)	83 lm/W				
LED flux maintenance	50000 hr, L 70, B 50				
		MECHANICAL CHARACTERISTICS			
Impact resistance rating (IK)	IK08				
IP	65				

PHOTOMETRIC DATA





Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Saturday, February 17, 2024

Code: 420665-00			MATERIALS AND COLOURS
		Housing	thermoplastic material, shatterproof, UV stabilised, RAL7045 grey colour.
		Optics	anodised and polished 99.85 aluminium.
0	225	Diffuser	in anti-glare matt polycarbonate, shatterproof and V2 self-extinguishing, UV stablised, anti-yellowing, externally smooth and dustproof.
		Pole connection	0
		Colour	Black
300		Equipment	- complete with fixing plate. - EPDM foam bowl gasket. - external screws in galvanised stainless steel with black OR.
			STANDARDS AND COMPLIANCE
	142	Photobiological safety class	RG0
	-	Markings and tests	CE
		Reference standards	EN60598-1. With degree of protection according to EN60529.
	DOWNLOAD	Energy Label	F
MOUNTS			GEAF
AssemblyInstructions 12	264 03-23.pdf	Upon request	0
DESIGNS			WARRANT
BIM 1264 Vega - 20200623.zip			
TechnicalDrawing 1264.dxf		After sales warranty	3 yr



╶┼┼

illuminazione

Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Saturday, February 17, 2024

Code: 420665-00



1266 Joint



5 Fibreglass pole





字

EXIT

Self-adhesive pictograms - 1260

95140-00 995141-00

995142-00 995143-00

Ż