1264 - Vega LED

Code: 420665-07





The Vega wall sconce, one of Disano's most popular wall lamps, combines excellent material quality and distinctive design with LED technology, which guarantees energy savings and long life. The unique shape of its housing allows for simple and functional installations. Also available with presence sensor to enhance functionality and service life.



		GENERAL INFORMATION
Article	1264 - Vega LED	
Code	420665-07	
		DIMENSIONS AND WEIGHT
Length (mm)	300 mm	
Width (mm)	225 mm	
Height (mm)	142 mm	
Weight (Kg)	1.840 kg	
		ELECTRICAL CHARACTERISTICS AND CONTROLS
Voltage type	AC	
Min Voltage (V)	220 V	
Max Voltage (V)	240 V	
Min Frequency (Hz)	50 Hz	
Max Frequency (Hz)	60 Hz	
Frequency (Hz)	50 Hz	
Wiring name	CLD-E	
Power factor	≥0.9	



Controllability

None

1264 - Vega LED


Code: 420665-07 PHOTOMETRIC DATA

Impact resistance rating (IK)

ΙP

IK08

65




CRI 70 Luminous flux (output) (lm) 1657 lm Power absorption (total) (W) 23 W CCT 4000 K Luminous efficacy (lm/W) 72 lm/W LED flux maintenance 50000 hr, L 70, B 50			MECHANICAL CHARACTERISTICS
CRI 70 Luminous flux (output) (lm) 1657 lm Power absorption (total) (W) 23 W CCT 4000 K	LED flux maintenance	50000 hr, L 70, B 50	
CRI 70 Luminous flux (output) (lm) 1657 lm Power absorption (total) (W) 23 W	Luminous efficacy (lm/W)	72 lm/W	
CRI 70 Luminous flux (output) (lm) 1657 lm	ССТ	4000 K	
CRI 70	Power absorption (total) (W)	23 W	
	Luminous flux (output) (lm)	1657 lm	
5 5	CRI	70	
Lighting source LED	Lighting source	LED	








Code: 420665-07





Housing	thermoplastic material, shatterproof, UV stabilised, RAL7045 grey colour.
Optics	anodised and polished 99.85 aluminium.
Diffuser	in anti-glare matt polycarbonate, shatterproof and V2 self-extinguishing, UV stablised, anti-yellowing, externally smooth and dustproof.
Pole connection	0
Colour	Black
Equipment	- complete with fixing plate. - EPDM foam bowl gasket. - external screws in galvanised stainless steel with black OR.

EMERGENCY LIGHTING

MATERIALS AND COLOURS

Type of emergency	S.A.
Battery life-recharge	1h

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0	
Markings and tests	CE	
Reference standards	EN60598-1. With degree of protection according to EN60529.	
Energy Label	F	
		GEAR
Upon request	0	
		WARRANTY
After sales warranty	3 yr	

DOWNLOAD

	INITO
MOL	JNTS

AssemblyInstructions 1264 03-23.pdf

DESIGNS

BIM 1264 Vega - 20200623.zip

TechnicalDrawing 1264.dxf





1264 - Vega LED

Code: 420665-07



1266 Joint









Self-adhesive pictograms - 1260



5 Fibreglass pole

