1264 - Vega LED

Code: 420666-00





The Vega wall sconce, one of Disano's most popular wall lamps, combines excellent material quality and distinctive design with LED technology, which guarantees energy savings and long life. The unique shape of its housing allows for simple and functional installations. Also available with presence sensor to enhance functionality and service life.



		GENERAL INFORMATION
Article	1264 - Vega LED	
Code	420666-00	
		DIMENSIONS AND WEIGHT
Length (mm)	300 mm	
Width (mm)	225 mm	
Height (mm)	142 mm	
Weight (Kg)	1.500 kg	
		ELECTRICAL CHARACTERISTICS AND CONTROLS
Voltage type	AC	
Min Voltage (V)	220 V	
Max Voltage (V)	240 V	
Min Frequency (Hz)	50 Hz	
Max Frequency (Hz)	60 Hz	
Frequency (Hz)	50 Hz	
Wiring name	CLD	
Power factor	≥0.9	

Class I

None

GENERAL INFORMATION



Insulation class

Controllability

1264 - Vega LED

Code: 420666-00
715:
1053
96
85
75
160
55
45"

ΙP


Lighting source	LED	
CRI	70	
Luminous flux (output) (lm)	1657 lm	
Power absorption (total) (W)	20 W	
CCT	4000 K	
Luminous efficacy (lm/W)	83 lm/W	
LED flux maintenance	50000 hr, L 70, B 50	
		MECHANICAL CHARACTERISTICS
Impact resistance rating (IK)	IK08	


65

PHOTOMETRIC DATA









DOWNI	OAD

After sales warranty

3 yr

MOUNTS

AssemblyInstructions 1264 03-23.pdf

DESIGNS

BIM 1264 Vega - 20200623.zip

TechnicalDrawing 1264.dxf



Housing	thermoplastic material, shatterproof, UV stabilised, RAL7045 grey colour.
Optics	anodised and polished 99.85 aluminium.
Diffuser	in anti-glare matt polycarbonate, shatterproof and V2 self-extinguishing, UV stablised, anti-yellowing, externally smooth and dustproof.
Pole connection	0
Colour	Grey
Equipment	 complete with fixing plate. EPDM foam bowl gasket. external screws in galvanised stainless steel with black OR.

MATERIALS AND COLOURS

STANDARDS AND COMPLIANCE
RG0
CE
EN60598-1. With degree of protection according to EN60529.
F
GEAR
0
WARRANTY



1264 - Vega LED

Code: 420666-00



1266 Joint









Self-adhesive pictograms - 1260



5 Fibreglass pole

