Code: 420666-07



The Vega wall sconce, one of Disano's most popular wall lamps, combines excellent material quality and distinctive design with LED technology, which guarantees energy savings and long life. The unique shape of its housing allows for simple and functional installations. Also available with presence sensor to enhance functionality and service life.




		GENERAL INFORMATION
Article	1264 - Vega LED	
Code	420666-07	
		DIMENSIONS AND WEIGHT
Length (mm)	300 mm	
Width (mm)	225 mm	
Height (mm)	142 mm	
Weight (Kg)	1.860 kg	
		ELECTRICAL CHARACTERISTICS AND CONTROLS
Voltage type	AC	
Min Voltage (V)	220 V	
Max Voltage (V)	240 V	
Min Frequency (Hz)	50 Hz	
Max Frequency (Hz)	60 Hz	
Frequency (Hz)	50 Hz	
Wiring name	CLD-E	
Power factor	≥0.9	
Insulation class	Class I	
Controllability	None	



Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Saturday, February 17, 2024

Code: 420666-07



Lighting source	LED	
CRI	70	
Luminous flux (output) (Im)	1657 lm	
Power absorption (total) (W)	23 W	
ССТ	4000 K	
Luminous efficacy (lm/W)	72 lm/W	
LED flux maintenance	50000 hr, L 70, B 50	
		MECHANICAL CHARACTERISTICS
Impact resistance rating (IK)	IK08	

PHOTOMETRIC DATA






Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Saturday, February 17, 2024

Code: 420666-07

225

142

DOWNLOAD



AssemblyInstructions 1264 03-23.pdf

BIM 1264 Vega - 20200623.zip TechnicalDrawing 1264.dxf

	MATERIALS AND COLOURS		
Housing	thermoplastic material, shatterproof, UV stabilised, RAL7045 grey colour.		
Optics	anodised and polished 99.85 aluminium.		
Diffuser	in anti-glare matt polycarbonate, shatterproof and V2 self-extinguishing, UV stablised, anti-yellowing, externally smooth and dustproof.		
Pole connection	0		
Colour	Grey		
Equipment	 complete with fixing plate. EPDM foam bowl gasket. external screws in galvanised stainless steel with black OR. 		
	EMERGENCY LIGHTING		
Type of emergency	S.A.		
Battery life-recharge	1h		
	STANDARDS AND COMPLIANCE		
Photobiological safety class	RG0		
Markings and tests	CE		
Reference standards	EN60598-1. With degree of protection according to EN60529.		
Energy Label	F		
	GEAR		
Upon request	0		
	WARRANTY		
After sales warranty	3 yr		

MOUNTS

DESIGNS





Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Saturday, February 17, 2024

Code: 420666-07



1266 Joint



5 Fibreglass pole



Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Saturday, February 17, 2024

995142-00 995143-00

Self-adhesive pictograms - 1260