



Declaration of Performance (DoP)



Nr. DoP0091

1. Unique identification code for the product type:
See appendix 1 (page 2/2)
2. Intended use of the construction product:
Supply of data communication in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke.
3. Manufacturer:
**TKF (B.V. Twentsche Kabelfabriek)
Spinnerstraat 15
7481 KJ Haaksbergen
Netherlands
Tel.: +31(0)53 573 22 55
E-mail: info@tkf.eu
www.tkf.eu**
4. System of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 3**
5. Notified body: **NB 0402**
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Dca-s2,d2,a3	EN50575:2014/A1:2016
Dangerous substances	NPD	(EC) No 1907/2006 (REACH)

7. The performance of the product identified is in conformity with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in this document.

Signed for and on behalf of B.V. Twentsche Kabelfabriek by:


Alexander van der Lof
Managing Director

Haaksbergen, June 7, 2023



Nr. DoP0091

Appendix 1

Product type	Number of pairs	Conductor diameter [mm]	Conductor cross-section [mm ²]
RE-2X(st)Y Dca	1 to 36		0.5 to 1.3
RE-2X(st)YSWBY Dca	1 to 60	0.8 to 2.04	0.5 to 2.5
RE-2X(st)YSWAY Dca	1 to 60	0.8 to 1.57	0.5 to 1.5
RE-2X(st)YSWBY PiMF Dca	2 to 60	0.8 to 2.04	0.5 to 2.5
RE-2X(st)YSWAY PiMF Dca	2 to 60	0.8 to 1.57	0.5 to 1.5
XLPE-MS-MS-PVC-SWB-PVC Dca	2 to 60	0.8 to 2.04	0.5 to 2.5

Product type	Number of pairs	Conductor diameter [mm]	Conductor cross-section [mm ²]
RE-2X(st)YSWAY Dca	3 to 60	2.04	2.5
RE-2X(st)YSWAY PiMF Dca	3 to 60	2.04	2.5

Product type	Number of triples	Conductor diameter [mm]	Conductor cross-section [mm ²]
RE-2X(st)Y Dca	6		1.3
RE-2X(st)YSWBY Dca	1 to 40	0.8 to 2.04	0.5 to 2.5
RE-2X(st)YSWAY Dca	1 to 40	0.8 to 1.57	0.5 to 1.5
RE-2X(st)YSWBY TiMF Dca	2 to 40	0.8 to 2.04	0.5 to 2.5
RE-2X(st)YSWAY TiMF Dca	2 to 40	0.8 to 1.57	0.5 to 1.5

Product type	Number of triples	Conductor diameter [mm]	Conductor cross-section [mm ²]
RE-2X(st)YSWAY Dca	3 to 40	2.04	2.5
RE-2X(st)YSWAY TiMF Dca	3 to 40	2.04	2.5