



Description: To replace the standard door, it provides a clear view of the components installed inside the enclosure. The lock(s) are interchangeable with all nVent HOFFMAN's standard lock(s).

Material: 1.2 mm mild steel / 1.5 mm for enclosures with a height or width of 500 mm or greater / 2 mm for enclosures with a height or width of 800 mm or greater and 4 mm clear safety glass.

Finish: RAL 7035 structured powder coating.

Protection: Complies with IP 55 | TYPE 12, 13, IK 07.

Pack quantity: 1 door.

H	W	VA h	VA w	N° of locks	Item no.
300	250	159	93	1	AD-C03025R5
300	300	159	143	1	AD-C03030R5
400	300	259	143	1	AD-C04030R5
400	400	259	243	1	AD-C04040R5
500	300	359	143	1	AD-C05030R5
500	400	359	243	1	AD-C05040R5
600	400	459	243	2	AD-C06040R5
600	500	459	343	2	AD-C06050R5
600	600	459	443	2	AD-C06060R5
700	500	559	343	2	AD-C07050R5
800	600	659	443	2	AD-C08060R5
1000	600	859	427	1*	AD-C10060R5
1000	800	859	627	1*	AD-C10080R5
1200	600	1059	427	1*	AD-C12060R5
1200	800	1059	627	1*	AD-C12080R5

* 3 point espagnolette locking.
Not suitable for AFS.