



This adjustable temperature thermostat, ETR, for any enclosure, with either a normally open (NO) or normally closed (NC) contact, is used to control installed devices. Such devices could be a filter fan or a fan heater, that should turn on or off at the required temperature level, set by the user. The result is reduced operational cost.



IP 20

Description	Normally opened contact
Weight (kg)	0.05
Item no.	ETR201

**Description:** Thermostat with NC/NO contacts to manage temperature in panels. ETR202 with a normally closed contact for regulating heaters. ETR201 with a normally open contact for regulating cooling devices or signal devices. Sensor element thermostatic bimetal. Mounting clip for 35 mm DIN rail (EN 60715).

**Material:** Plastic according to UL94 V-0.

**Setting range:** 0 °C to +60 °C. Switching temperature difference less than 7 °K, and switching point tolerance  $\pm 4$  °K.

**Switch capacity:** 240 V AC, 10(2) A. 120 V AC, 15(2) A. 24 V DC, 30 W. Value in brackets for inductive load.

**Operating temperature:** -20 °C to +80 °C.

**Service life:** > 100,000 cycles.

**Connection:** Screw terminal for cable (0.5 to 2.5 mm<sup>2</sup>).

**Protection:** IP 20.

**Approvals:** CE, EAC, cULus\_UL Listed.

**Finish:** RAL 7035.

**Pack quantity:** 1 piece.