



This dual adjustable temperature thermostat, ETR203, for any enclosure, houses two independent thermostats, which reduces space requirements within the enclosure. One has a normally open (NO) contact, and one has a normally closed (NC) contact, which means that one thermostat's temperature setting could control cooling and the other thermostat could control heating. The devices controlled, such as a filter fan or a fan heater, will then turn on or off at the required temperature level, set by the user, which results in reduced operational cost.

CE EAC

IP 20

Table 1

Weight (kg)	0.10
Item no.	ETR203

Description: Device with two independent thermostats, unlike thermostats with changeover contacts, connected devices can be switched in different temperature ranges. One thermostat with a normally closed contact for regulating heaters, and one with a normally opened contact for regulating cooling devices or signal devices. Sensor element thermostatic bimetal. Mounting clip for 35 mm DIN rail (EN 60715).

Material: Plastic according to UL94 V-0.

Setting range: 0 °C to +60 °C. Switching temperature difference less than 7 °K, and switching point tolerance ± 4 °K.

Switch capacity: 240 V AC, 10(2) A. 120 V AC, 15(2) A. 24 V DC, 30 W. Value in brackets for inductive load.

Operating temperature: -40 °C to +80 °C.

Service life: > 100,000 cycles.

Connection: Screw terminal for cable (0.5 to 2.5 mm²).

Protection: IP 20.

Approvals: CE, EAC, cULus_UL Listed.

Finish: RAL 7035.

Pack quantity: 1 piece.