# KABELFRAME, 200X1200X500, COMBINEERBAAR

## CATALOGUSNUMMER

**MCU2125R5**



Dit frame, dat zorgt voor extra ruimte in het bovengedeelte, kan worden afgescheiden van de behuizing. Het heeft een universeel gatenpatroon voor een eenvoudige montage van accessoires.

## KENMERKEN

Omschrijving: Voor kabelinvoer en routing of voor installatie van een voedingsverdeelsysteem. Bevestigd aan de bovenzijde van de behuizing door vier M12 schroeven. Leverbaar in zowel 200 mm en 300 mm hoogte. De dakplaat van de behuizing (CCR) kan gebruikt worden als afdekplaat. Voor het hijsen van een 200 mm hoge MCU samen met een behuizing is een separate hijskit nodig (MCUK).

Zijwanden: MCUP wordt als accessoire geleverd.

Materiaal: Frame van 1,75 mm plaatstaal, panelen in 1,35 mm plaatstaal.

Afwerking: Structuur poedercoating, RAL 7035.

Beschermingsklasse: Overeenkomstig IP 41.

Verpakkingseenheid: Per stuk, met front- en achterpanelen, inclusief bevestigingsmateriaal (zonder dakplaat).

Top extension frame for mild steel combinable floor standing enclosures

The frame creates additional space at the top of the enclosure with integrated hole patterns and allows segregation if required

The frame can be segregated from the enclosure which creates extra space for hazardous components, for example main busbars

Standard accessories can be mounted within the frame thanks to the universal hole pattern allowing accessories to be easily mounted, e.g. busbar supports

Side panels MCUP, are required at the beginning and end of the individual or bayed top extension frames

Pack quantity: 1 piece with front and back panels including mounting accessories (without roof plate)

## PRODUCTKENMERKEN

Hoogte: 200 mm

Breedte: 1200 mm

Diepte: 500 mm

Materiaal: Plaatstaal

Finish: Plated

Kleur: Lichtgrijs

Color Code: RAL 7035

Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.