



SITOP UPS1600/DC/24VDC/20A/IE/PN

SITOP UPS1600 20 A Ethernet/ PROFINET uninterruptible power supply with Ethernet / PROFINET interface / OPC UA server / web server input: 24 V DC output: 24 V DC/20 A *Ex approval no longer available*

input	
supply voltage at DC rated value	24 V
input voltage	DC 21 ... 29 V
adjustable response value voltage for buffer connection preset	21.5 V
adjustable response value voltage for buffer connection	21 ... 25 V; Adjustable: 21 V, 21.5 V, 22 V, 22.5 V, 23 V, 24 V, 25 V DC or via software
input current at rated input voltage 24 V rated value	25 A; for max. charging current (4 A)
memory	
type of energy storage	with batteries
design of the mains power cut bridging-connection	Adjustable range using rotary coding switch: 0.5 min, 1 min, 2 min, 5 min, 10 min, 20 min, max. buffering time or via software
output	
output voltage	
• in normal operation at DC rated value	24 V
• in buffering mode at DC rated value	24 V
formula for output voltage	$V_{in} - \text{approx. } 0.2 \text{ V}$
startup delay time typical	60 ms
voltage increase time of the output voltage typical	60 ms
output voltage in buffering mode at DC	18.5 ... 27 V
output current	
• rated value	20 A
• in normal operation	0 ... 60 A
• in buffering mode	0 ... 60 A
peak current	60 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Limitation to 3 x I rated for 30 ms/min; through-conductivity for 1.5 x I rated for 5 sec/min
charging current	0.1 A, 4 A; Automatically depending on battery module
power loss	
efficiency in percent	
• at rated output voltage for rated value of the output current typical	97.5 %
• in case of operation on rechargeable battery typical	97.5 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	11 W
• in case of operation on rechargeable battery typical	11 W
supplied active power typical	480 W
protection and monitoring	
product function	
• reverse polarity protection against energy storage unit polarity reversal	Yes

• reverse polarity protection against input voltage polarity reversal	Yes
display version	Normal operation: LED green (OK), floating changeover contact "Bat/OK" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); Lack of buffer standby: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Battery replacement required: LED red (alarm) flashing with approx. 0.25 Hz, floating changeover contact "Alarm/Bat" switching with approx. 0.25 Hz; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed; Permissible contact current capacity: DC 60 V/1 A or AC 30 V /1 A Buffered mode: LED yellow (Bat), floating changeover contact "OK/Bat" to setting "Bat"; Prewarning battery voltage < 20.4 VDC: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed
• for normal operation	
• in buffering mode	
interfaces	
product component PC interface	Yes
product function communication function	Yes
design of the interface	Ethernet/PROFINET
number of interfaces according to PROFINET	2
safety	
galvanic isolation between input and output	No
operating resource protection class	Class III
protection class IP	IP20
standard	EN 55022 Class B EN 61000-6-2
• for emitted interference • for interference immunity	
standards, specifications, approvals	
certificate of suitability	Yes Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259 Yes Yes
• CE marking	
• UL approval	
• CSA approval	
• EAC approval	Yes
type of certification CB-certificate	Yes
MTBF at 40 °C	345 056 h
standards, specifications, approvals hazardous environments	
certificate of suitability	No No
• ATEX • cCSAus, Class 1, Division 2	
standards, specifications, approvals marine classification	
shipbuilding approval	Yes
Marine classification association	Yes Yes
• American Bureau of Shipping Europe Ltd. (ABS) • Det Norske Veritas (DNV)	
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	365.5 kg 20.9 kg 344.2 kg 0.33 kg
• total	
• during manufacturing	
• during operation	
• after end of life	0.33 kg
ambient conditions	
ambient temperature	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
• during operation	
• during transport	
• during storage	
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	screw-type terminals
• at input	24 V DC: 2 screw terminals for 0.2 ... 6 mm²/24 ... 13 AWG
• at output	24 V DC: 2 screw terminals for 0.2 ... 6 mm²/24 ... 13 AWG
• for rechargeable battery module	24 V DC: 2 screw terminals for 0.2 ... 6 mm²/24 ... 13 AWG
• for control circuit and status message	14 screw terminals for 0.2 ... 1.5 mm²/24 ... 16 AWG

mechanical data			
width × height × depth of the enclosure	50 × 139 × 125 mm		
installation width × mounting height	50 × 239 mm		
required spacing			
• top	50 mm		
• bottom	50 mm		
• left	0 mm		
• right	0 mm		
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15		
• standard rail mounting	Yes		
• S7 rail mounting	No		
• wall mounting	No		
housing can be lined up	Yes		
net weight	0.45 kg		
accessories			
electrical accessories	Battery module		
further information internet links			
internet link			
• to website: Industry Mall	https://mall.industry.siemens.com		
• to web page: selection aid TIA Selection Tool	https://siemens.com/tst		
• to website: Industrial communication	http://www.siemens.com/simatic-net		
• to website: CAX-Download-Manager	http://www.siemens.com/cax		
• to website: Industry Online Support	https://support.industry.siemens.com		
additional information			
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)		
security information			
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)		
Classifications			
		Version	Classification
	eClass	12	27-04-07-05
	eClass	9.1	27-04-07-05
	eClass	9	27-04-07-05
	eClass	8	27-04-06-90
	eClass	7.1	27-04-06-90
	eClass	6	27-04-06-90
	ETIM	9	EC000382
	ETIM	8	EC000382
	ETIM	7	EC000382
	IDEA	4	4149
	UNSPSC	15	39-12-10-11
Approvals Certificates			
General Product Approval			



[Manufacturer Declaration](#)

[Declaration of Conformity](#)



[PROFINET](#)

General Product Approval	For use in hazardous locations	Marine / Shipping
--------------------------	--------------------------------	-------------------



[CCC-Ex](#)



Marine / Shipping	other	Environment
-------------------	-------	-------------



[Miscellaneous](#)



last modified:

3/25/2024