



Connection terminal Cable entry left 690V AC, 1000 V DC, 125 A IP20

Model	
product brand name	SENTRON
product designation	Busbar systems
design of the product	Accessories
Supply voltage	
operating voltage at AC rated value	690 V
Connections	
tightening torque	
• minimum	1 N·m
• maximum	3.5 N·m
type of connectable conductor cross-sections for copper conductor stranded	6-50 mm <sup>2</sup>
Mechanical Design	
height	27 mm
width	20 mm
depth	16.5 mm
length	30 mm
net weight	23.3 g
Approvals Certificates	
General Product Approval	other



[Confirmation](#)



EG-Konf.

[Miscellaneous](#)



[Miscellaneous](#)

other	Environment
<a href="#">Confirmation</a>	<a href="#">Environmental Confirmations</a>
	<a href="#">Environmental Confirmations</a>

**Further information**

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information- and Downloadcenter (Catalogs, Brochures,...)  
<http://www.siemens.com/lowvoltage/catalogs>  
 Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3760-4>  
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/5ST3760-4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5ST3760-4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5ST3760-4)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

---

last modified:

3/12/2024 

