



Sub-family of Harmony XVR pre-wired rotating/flashing beacons

Harmony XVR3

Harmony XVR3 are range of High visibility beacon/rotating mirror design for providing industrial visual warnings and signals



All-in-one light pattern, motorless XVR3 family
Ø 100 beacon offer that serves your industrial needs

1 Efficient and Safe

- Long life thanks to motorless LED Flashing
- High protection up to IP65
- Vibration resistance up to 7.1g

2 Unique design



reddot award
winner industrial design



3 Easy to stock

- Rotating, blinking, flashing (three modes in one)
- One reference = 10 applications

Compliances



se.com

Life Is On

Schneider
Electric

XVR3 Rotating Beacon offer overview

- Light mode selector – 10 modes in one: rotating, Blinking and flashing
- Motherless + LED flashing
- High protection of up to IP65
- Conformity with IEC, UL, CSA standards as well as CE marking
- External buzzer volume adjustor, up to 90dB
- Supports multiple mounting option
- Wide voltage range Supports both 12-24VDC and 100 -230VAC

Mode 0		Rotating 100 min ⁻¹
Mode 1	Rotating	Rotating 140 min ⁻¹
Mode 2		Rotating 200 min ⁻¹
Mode 3	Blinking	Blinking 60 min ⁻¹
Mode 4		Blinking 130 min ⁻¹
Mode 5		Flashing 3 times consecutively
Mode 6		Flashing 5 times consecutively
Mode 7	Flashing	Flashing 8 times consecutively
Mode 8		Flashing 11 times consecutively
Mode 9		Flashing continuously

Beacon lights with buzzer, multi-functional beacon lights

LED unit type	Beacon			
Color	● Green	● Red	● Orange	● Blue
Voltage	12-24 VDC			
Reference	XVR3B03S	XVR3B04S	XVR3B05S	XVR3B06S
Voltage	100-230 VAC			
Reference	XVR3M03S	XVR3M04S	XVR3M05S	XVR3M06S

Beacon lights without buzzer

LED unit type	Beacon			
Color	● Green	● Red	● Orange	● Blue
Voltage	12-24 VDC			
Reference	XVR3B03	XVR3B04	XVR3B05	XVR3B06
Voltage	48 VDC			
Reference	XVR3E03	XVR3E04	XVR3E05	XVR3E06
Voltage	100-230 VAC			
Reference	XVR3M03	XVR3M04	XVR3M05	XVR3M06

se.com



Life Is On

Schneider
Electric

Schneider Electric Industries SAS
35 rue Joseph Monier
92500 Rueil-Malmaison, France
Tel : +33 (0)1 41 29 70 00