

Eaton 293988

Catalog Number: 293988

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 12.5 kVAr, 230 V 50 Hz, 240 V 60 Hz



General specifications

Product Name	Catalog Number
Eaton Moeller® series DILK capacity contactor	293988
	Model Code
	DILK12-11(230V50HZ,240V60HZ)
EAN	Product Length/Depth
4015082939885	138 mm
Product Height	Product Width
135 mm	45 mm
Product Weight	Warranty
0.51 kg	1 year

Certifications

CSA File No.: 012528
CE
CSA-C22.2 No. 60947-4-1-14
UL Category Control No.: NLDX
UL File No.: E29096
IEC/EN 60947
UL
UL 60947-4-1
IEC/EN 60947-4-1
CSA
CSA Class No.: 3211-04

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

Catalogs

[Product Range Catalog Switching and protecting motors](#)

[SmartWire-DT Catalog](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

Declarations of conformity

[DA-DC-00004785.pdf](#)

[DA-DC-00004814.pdf](#)

Drawings

[eaton-contactors-dilk-dimensions-004.eps](#)

[eaton-contactors-mounting-dilm-dimensions.eps](#)

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)

[eaton-contactors-dilk-dimensions-002.eps](#)

[eaton-contactors-dilk-dimensions.eps](#)

[eaton-contactors-dilk-3d-drawing.eps](#)

eCAD model

[DA-CE-ETN.DILK12-11\(230V50HZ,240V60HZ\)](#)

Installation instructions

[IL03407038Z](#)

Installation videos

[WIN-WIN with push-in technology](#)

mCAD model

[eaton-dilk12-25-3d-model.stp](#)

[eaton-dilk12-25-drawing.dwg](#)

[DA-CD-dil_m17_38](#)

[DA-CS-dil_m17_38](#)

Specifications and datasheets

[Eaton Specification Sheet - 293988](#)

Wiring diagrams

[eaton-contactors-circuit-dilk-wiring-diagram-002.eps](#)

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Series resistors

Operating frequency

120 Operations/h

Ambient operating temperature - max

60 °F

Ambient operating temperature - min

-25 °F

Ambient operating temperature (enclosed) - max

40 °F

Ambient operating temperature (enclosed) - min

25 °F

Equipment heat dissipation, current-dependent P_{vid}

2.1 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0.7 W

Number of auxiliary contacts (normally closed contacts)

1

Number of auxiliary contacts (normally open contacts)

1

Number of contacts (normally closed) as main contact

0

Number of main contacts (normally open contact)

3

Rated control supply voltage (Us) at AC, 50 Hz - max

230 V

Rated control supply voltage (Us) at AC, 50 Hz - min

230 V

Rated control supply voltage (Us) at AC, 60 Hz - max

240 V

Rated control supply voltage (Us) at AC, 60 Hz - min

240 V

Rated control supply voltage (Us) at DC - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated operational current for specified heat dissipation (In)

18 A

Connection

Screw terminals

Static heat dissipation, non-current-dependent Pvs

2.1 W

Switching time (AC operated, make contacts, closing delay) - max

22 ms

Switching time (AC operated, make contacts, closing delay) - min

16 ms

Switching time (AC operated, make contacts, opening delay) - max

14 ms

Application

Contactors for power factor correction

Product category

DILK Contactors for capacitors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Number of auxiliary contacts (change-over contacts)

0

Rated switch current

18 A

Operating voltage at AC, 50 Hz - min

230 V

Operating voltage at AC, 50 Hz - max

690 V

Operating voltage at AC, 60 Hz - min

230 V

Operating voltage at AC, 60 Hz - max

690 V

Rated blind power at 400 V, 60 Hz

12.5 W

Arcing time

10 ms

Electrical connection type of main circuit

Screw connection

Voltage type

AC

Degree of protection

IP00

Drop-out voltage

AC operated: 0.6 - 0.3 x UC, AC operated

Duty factor

100 %

Emitted interference

According to EN 60947-1

Interference immunity

According to EN 60947-1

Lifespan, electrical

150,000 Operations

Making capacity without damping (I-peak value)

180 x I_e

Pick-up voltage

0.8 - 1.1 V AC x U_c

Power consumption, pick-up, 50 Hz

58 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Power consumption, pick-up, 60 Hz

71 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Power consumption, sealing, 50 Hz

2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

7.6 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Power consumption, sealing, 60 Hz

9.3 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Rated blind power

12.5 kvar

Rated operational current (Ie)

18 A at 400 V (three-phase capacitors, open)

18 A at 525 V (three-phase capacitors, open)

18 A at 230 V (three-phase capacitors, open)

18 A at 690 V (three-phase capacitors, open)

16 A at 525 V (three-phase capacitors, enclosed)

16 A at 690 V (three-phase capacitors, enclosed)

16 A at 400 V (three-phase capacitors, enclosed)

16 A at 230 V (three-phase capacitors, enclosed)

Special purpose rating of capacitor switching

18 A, 240 V 60 Hz 3phase, (UL/CSA)

15 kVar, 600 V 60 Hz 3phase, (UL/CSA)

7.5 kVar, 240 V 60 Hz 3phase, (UL/CSA)

15 kVar, 480 V 60 Hz 3phase, (UL/CSA)

18 A, 480 V 60 Hz 3phase, (UL/CSA)

14.4 A, 600 V 60 Hz 3phase, (UL/CSA)

Terminal capacity (stranded)

1 x 16 mm², Main cables

Switching capacity (auxiliary contacts, general use)

10 A, 600 V AC, (UL/CSA)

1 A, 250 V DC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)

P300, DC operated (UL/CSA)

Terminal capacity (flexible with ferrule)

1 x (0.75 - 16) mm², Main cables

Terminal capacity (solid)

1 x (0.75 - 16) mm², Main cables

Terminal capacity (solid/stranded AWG)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)