

Eaton 208214

Catalog Number: 208214

Eaton Moeller® series DILM Contactor, 380 V 400 V 265 kW, 2 N/O, 2 NC, RAC 500: 250 - 500 V 40 - 60 Hz/250 - 700 V DC, AC and DC operation, Screw connection

General specifications



Product Name	Catalog Number
Eaton Moeller® series DILM Contactor	208214
Model Code	EAN
DILM500/22(RAC500)	4015082082147
Product Length/Depth	Product Height
216 mm	219 mm
Product Width	Product Weight
160 mm	8.662 kg
Certifications	Catalog Notes
IEC/EN 60947-4-1	Contacts
VDE 0660	according to EN
UL Category Control No.: NLDX	50012
UL 60947-4-1	Also tested
UL File No.: E29096	according to AC-
CSA Class No.: 3211-04	3e up to 500 V.
UL/CSA	Also suitable for
CSA file No. 012528	motors with
North America (UL listed, CSA certified)	efficiency class
EN 45545: Fire protection on railway	IE3.
vehicles	EN 45545 - Fire
IEC 61373: Vibration and shock, tested	protection on
for category 1 class B	railway vehicles:
CE marking	Fire protection
	class of all
	plastics
	according to
	UL94: V-0 /

Accessories

Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be

Catalogs

Product Range Catalog Switching and protecting motors

Switching and protecting motors - catalog

Characteristic curve

[eaton-contactors-component-dilm-characteristic-curve-003.eps](#)

[eaton-contactors-component-dilm-characteristic-curve-002.eps](#)

[eaton-contactors-short-time-loading-dilm-characteristic-curve-002.eps](#)

[eaton-contactors-component-dilm-characteristic-curve.eps](#)

Declarations of conformity

[DA-DC-00004804.pdf](#)

[DA-DC-00004796.pdf](#)

Drawings

[eaton-contactors-dilm-dimensions-009.eps](#)

[eaton-contactors-mounting-dilm-dimensions.eps](#)

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)

[eaton-contactors-mounting-dilm-3d-drawing-002.eps](#)

[eaton-contactors-dilm-3d-drawing-005.eps](#)

eCAD model

[DA-CE-ETN.DILM500_22\(RAC500\)](#)

Installation instructions

[IL03406002Z](#)

mCAD model

[DA-CD-dil_m500_570](#)

[DA-CS-dil_m500_570](#)

Specifications and datasheets

[Eaton Specification Sheet - 208214](#)

Wiring diagrams

[eaton-contactors-contact-dilm-wiring-diagram-004.eps](#)

evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Suppressor circuit in actuating electronics

Operating frequency

200 Operations/h

2000 mechanical Operations/h (AC operated)

2000 mechanical Operations/h (DC operated)

Pollution degree

3

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Rated impulse withstand voltage (Uimp)

8000 V AC

Utilization category

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

Connection

Screw terminals

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-40 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

-40 °C

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

-40 °C

Assigned motor power at 230/240 V, 60 Hz, 3-phase

200 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

400 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

500 HP

Conventional thermal current i_{th} (1-pole, enclosed)

1500 A

Conventional thermal current i_{th} (3-pole, enclosed)

600 A

Conventional thermal current i_{th} at 55°C (3-pole, open)

682 A

Conventional thermal current i_{th} of main contacts (1-pole, open)

1625 A

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

19.33 W

Application

Contactors for Motors

Product category

Contactors

Protection

Finger and back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated from front (EN 50274)

Electrical connection type of main circuit

Rail connection

Screwdriver size

2, Terminal screw, Control circuit cables, Pozidriv screwdriver

Voltage type

AC/DC

Degree of protection

IP00

Number of auxiliary contacts (normally closed contacts)

2

Number of auxiliary contacts (normally open contacts)

2

Number of contacts (normally closed contacts)

2

Number of contacts (normally closed) as main contact

0

Number of contacts (normally open contacts)

2

Number of main contacts (normally open contact)

3

Rated breaking capacity at 1000 V

950 A

Rated breaking capacity at 220/230 V

5000 A

Rated breaking capacity at 380/400 V

5000 A

Rated breaking capacity at 500 V

5000 A

Rated breaking capacity at 660/690 V

5000 A

Rated control supply voltage (Us) at AC, 50 Hz - max

500 V

Rated control supply voltage (Us) at AC, 50 Hz - min

250 V

Rated control supply voltage (Us) at AC, 60 Hz - max

500 V

Rated control supply voltage (Us) at AC, 60 Hz - min

250 V

Drop-out voltage

AC operated: $0.2 \times U_{S \text{ max}} - 0.6 \times U_{S \text{ min}}$, AC operated

$0.2 \times U_{S \text{ max}} - 0.6 \times U_{S \text{ min}}$, DC operated

Overvoltage category

III

Behavior in marginal and transitional conditions

Sealing - Pick-up phase ($0 - 0.7 \times U_{c \text{ min}}$): Contactor does not switch on

Sealing - Excess voltage ($1.15 - 1.3 \times U_{c \text{ max}}$): Contactor remains switched on

Sealing - Voltage drops ($0.2 - 0.6 \times U_{c \text{ min}} \leq 12 \text{ ms}$): Time is bridged successfully

Sealing - Voltage drops ($0.6 - 0.7 \times U_{c \text{ min}}$): Contactor remains switched on

Sealing - Pick-up phase ($0.7 \times U_{c \text{ min}} - 1.15 \times U_{c \text{ max}}$):
Contactor switches on with certainty

Sealing - Voltage interruptions ($0 - 0.2 \times U_{c \text{ min}} \leq 10 \text{ ms}$):
Time is bridged successfully

Sealing - Voltage drops ($0.2 - 0.6 \times U_{c \text{ min}} > 12 \text{ ms}$): Drop-out of the contactor

Sealing - Voltage interruptions ($0 - 0.2 \times U_{c \text{ min}} > 10 \text{ ms}$): Drop-out of the contactor

Duty factor

100 %

Electromagnetic compatibility

Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression.

Lifespan, mechanical

7,000,000 Operations (AC operated)

7,000,000 Operations (DC operated)

Pick-up voltage

$0.7 - 1.15 \text{ V DC} \times U_{S}$

$0.7 - 1.15 \text{ V AC} \times U_{S}$

Power consumption, pick-up, 50 Hz

350 W, Pull-in power, Coil in a cold state and $1.0 \times U_{S}$

450 VA, Pull-in power, Coil in a cold state and 1.0 x Us

Safe isolation

1000 V AC, Between coil and contacts, According to EN 61140

Power consumption, pick-up, 60 Hz

450 VA, Pull-in power, Coil in a cold state and 1.0 x Us

350 W, Pull-in power, Coil in a cold state and 1.0 x Us

Screw size

M3.5, Terminal screw, Control circuit cables

M10, Terminal screw, Main connections

Power consumption, sealing, 50 Hz

19.6 VA, Coil in a cold state and 1.0 x Us

11.7 W, Coil in a cold state and 1.0 x Us

Power consumption, sealing, 60 Hz

11.7 W, Coil in a cold state and 1.0 x Us

19.6 VA, Coil in a cold state and 1.0 x Us

Resistance

500 m Ω (Admissible transitional contact resistance - of the external control circuit device when actuating A11)

Rated operational current (Ie)

307 A at up to 525 V (Individual compensation, three-phase capacitors, open)

177 A at 690 V (Individual compensation, three-phase capacitors, open)

Inrush current

Max. 30 x Ie (peak)

Switching capacity (auxiliary contacts, general use)

1 A, 250 V DC, (UL/CSA)

15 A, 600 V AC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

P300, DC operated (UL/CSA)

A600, AC operated (UL/CSA)

Lifespan, electrical

100,000 Operations (at Condensor operation)

Terminal capacity (copper band)

Fixing with flat cable terminal or cable terminal blocks; See terminal capacity for cable terminal blocks

Terminal capacity (flexible with ferrule)

2 x (0.75 - 2.5) mm², Control circuit cables

1 x (0.75 - 2.5) mm², Control circuit cables

Shock resistance

8 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Terminal capacity (solid)

1 x (0.75 - 2.5) mm², Control circuit cables
2 x (0.75 - 2.5) mm², Control circuit cables

Terminal capacity (solid/stranded AWG)

18 - 14, Control circuit cables
2/0 - 500 MCM, Main cables

Signal level

5 V - 15 V, PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2), Magnet systems

Terminal capacity (busbar)

30 mm width, Main connection

Terminal capacity (flexible with cable lug)

50 - 240 mm²

Switching capacity (main contacts, general use)

550 A, Maximum motor rating (UL/CSA)

Terminal capacity (stranded with cable lug)

70 - 240 mm²

Power consumption

Control transformer with $uk \leq 6\%$

Tightening torque

24 Nm, Main cable connection screw/bolt
1.2 Nm, Screw terminals, Control circuit cables

Width across flats

16 mm

Rated control supply voltage (Us) at DC - max

700 V

Rated control supply voltage (Us) at DC - min

250 V

Rated insulation voltage (Ui)

1000 V

Rated making capacity (cos phi to IEC/EN 60947)

5500 A

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V

800 A

Rated operational current (I_e) at AC-3, 1000 V

95 A

Rated operational current (I_e) at AC-3, 220 V, 230 V, 240 V

500 A

Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V

500 A

Rated operational current (I_e) at AC-3, 440 V

500 A

Rated operational current (I_e) at AC-3, 500 V

500 A

Rated operational current (I_e) at AC-3, 660 V, 690 V

325 A

Rated operational current (I_e) at AC-4, 1000 V

95 A

Rated operational current (I_e) at AC-4, 220 V, 230 V, 240 V

360 A

Rated operational current (I_e) at AC-4, 400 V

360 A

Rated operational current (I_e) at AC-4, 440 V

360 A

Rated operational current (I_e) at AC-4, 500 V

360 A

Rated operational current (I_e) at AC-4, 660 V, 690 V

260 A

Rated operational current for specified heat dissipation (I_n)

500 A

Rated operational power at AC-3, 1000 V, 50 Hz

132 kW

Rated operational power at AC-3, 240 V, 50 Hz

170 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

250 kW

Rated operational power at AC-3, 415 V, 50 Hz

290 kW

Rated operational power at AC-4, 1000 V, 50 Hz

132 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

112 kW

Rated operational power at AC-4, 240 V, 50 Hz

122 kW

Rated operational power at AC-4, 380/400 V, 50 Hz

200 kW

Rated operational power at AC-4, 415 V, 50 Hz

216 kW

Rated operational power at AC-4, 440 V, 50 Hz

229 kW

Rated operational power at AC-4, 500 V, 50 Hz

250 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

240 kW

Rated operational power (NEMA)

298 kW

Rated operational voltage (U_e) at AC - max

1000 V

Resistance per pole

0.089 mΩ

Static heat dissipation, non-current-dependent P_{vs}

11.7 W

Switching time (AC operated, make contacts, closing delay) - max

80 ms

Switching time (AC operated, make contacts, opening delay) - max

110 ms

Short-circuit current rating (basic rating)

30 kA, SCCR (UL/CSA)

800 A, max. Fuse, SCCR (UL/CSA)

600 A, max. CB, SCCR (UL/CSA)

Short-circuit current rating (high fault at 480 V)

30/100 kA, Fuse, SCCR (UL/CSA)

100 kA, CB, SCCR (UL/CSA)

600 A, max. CB, SCCR (UL/CSA)

800/600 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit current rating (high fault at 600 V)

800/600 A, Class J, max. Fuse, SCCR (UL/CSA)

30 kA, CB, SCCR (UL/CSA)
30/100 kA, Fuse, SCCR (UL/CSA)
600 A, max. CB, SCCR (UL/CSA)

Short-circuit protection rating (type 1 coordination) at 1000 V
250 A gG/gL

Short-circuit protection rating (type 1 coordination) at 400 V
630 A gG/gL

Short-circuit protection rating (type 1 coordination) at 690 V
630 A gG/gL

Short-circuit protection rating (type 2 coordination) at 1000 V
200 A gG/gL

Short-circuit protection rating (type 2 coordination) at 400 V
500 A gG/gL

Short-circuit protection rating (type 2 coordination) at 690 V
500 A gG/gL

Special purpose rating of definite purpose rating

520 A, FLA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)
3900 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)
3120 A, LRA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)
635 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)

Conventional thermal current i_{th} at 40°C (3-pole, open)
800 A

Conventional thermal current i_{th} at 50°C (3-pole, open)
715 A

Conventional thermal current i_{th} at 60°C (3-pole, open)
650 A

Rated operational power at AC-3, 440 V, 50 Hz
315 kW

Rated operational power at AC-3, 500 V, 50 Hz
355 kW

Rated operational power at AC-3, 690 V, 50 Hz
300 kW

Actuating voltage

RAC 500: 250 - 500 V 40 - 60 Hz/250 - 700 V DC

Altitude

Max. 2000 m

Operating voltage at AC, 50 Hz - min

250 V

Operating voltage at AC, 50 Hz - max

500 V

Operating voltage at AC, 60 Hz - min

250 V

Operating voltage at AC, 60 Hz - max

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)