

# Eaton XV-102-E6-57TVRC-10

Catalog Number: XV-102-E6-57TVRC-10

Eaton XV100 basic (HMI), Second generation CE plastic housing, XSoft-CoDeSys/Galileo OS, Retentive memory, USB host, SmartWire-DT base unit, CANopen communication, 5.7 in TFT resistive touch (VGA) display, Standard blank front bezel

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton XV100 basic human machine interface (HMI)	XV-102-E6-57TVRC-10
	<b>EAN</b>
	7640130097605

<b>Product Length/Depth</b>	<b>Product Height</b>
11 in	3.5 in

<b>Product Width</b>	<b>Product Weight</b>
7.5 in	1.2 lb

<b>Warranty</b>	<b>Compliances</b>
Eaton Selling Policy 25-000, one (1) year CE Marked from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	RoHS Compliant
	<b>Certifications</b>
	cULus Listed
	UL Listed

## Catalog Notes

All 1xx performance class units have 400MHz processor, 64 MB DRAM, 1x10/100 Ethernet, and 1x USB device.

Base unit

Retentive memory, USB host, SmartWire-DT

Bezel

Blank front

Communication

CANopen

Display

5.7 in TFT resistive touch (VGA)

Operating system

XSoft-CoDeSys

Galileo

Brochures

[XV and XP Series Operator Interfaces Product Aid - PA04801003E](#)

Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

Multimedia

[HMI-PLC overview](#)

Specifications and datasheets

[Eaton Specification Sheet - XV-102-E6-57TVRC-10](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)