



1.1

Miniature Circuit Breakers FAZ-HS

wa_sg00114





Description

FAZ-HS

- Tripping characteristic B
- Rated breaking capacity up to 10 kA according to IEC/EN 60898-1
- 1- and 2-poles available
- Miniature bircuit breaker with reduced Letthrough-energy for control circuits to protect the auxiliary switch contacts from welding.

Miniature Circuit Breakers

FAZ-...-HS Miniature Circuit Breakers

Rated Rated current voltage I_n (A) (V)

Breaking capacity acc. to IEC/EN 60898-1 (kA)

Type Designation

Article No. Units per package

Characteristic B

• Miniature bircuit breaker with reduced Let-through-energy for control circuits to protect the auxiliary switch contacts from welding.



| 1-pole | | | | | |
|--------|-----|----|-------------|--------|--------|
| 4 | 240 | 10 | FAZ-B4/1-HS | 279274 | 12/120 |

3-poles

4-poles



| 2-pole | s | | | |
|--------|-----|----|-------------|-------------|
| 4 | 240 | 10 | FAZ-B4/2-HS | 279275 1/60 |

| Miniature Circuit Breakers FAZ | | | | | |
|---|--------------|------------------------|--|--|--|
| Accessories: | | | | | |
| Auxiliary switch for subsequent installation | FAZ-XHIN11 | 286054 | | | |
| | FAZ-XHINW1 | 286055 | | | |
| Tripping signal contact for subsequent installation | FAZ-XAM002 | 262414 | | | |
| Shunt trip release | ZP-ASA/ | 248438, 248439 | | | |
| Undervoltage release | FAZ-XAA | 278518, 278519 | | | |
| | FAZ-XUA | 212049, 212051, 212053 | | | |
| Switching interlock | Z-IS/SPE-1TE | 274418 | | | |
| Terminal cover | | | | | |
| 1-pole | Z-TC/MCB-1P | 178102 | | | |
| 2-poles | Z-TC/SD-2P | 178099 | | | |

Z-TC/SD-3P

Z-TC/SD-4P

178100

178101

Eaton's electrical business is a global leader with deep regional application expertise in power distribution and circuit protection; power quality, backup power and energy storage; control and automation; life safety and security; structural solutions; and harsh and hazardous environment solutions. Through end-to-end services, channel and an integrated digital platform & insights Eaton is powering what matters across industries and around the world, helping customers solve their most critical electrical power management challenges.

For more information, visit **Eaton.com**.



Eaton Industries (Austria) GmbH Scheydgasse 42 1210 Vienna Austria

EatonEMEA Headquarters
Route de la Longeraie 7
1110 Morges, Switzerland

© 2021 Eaton All Rights Reserved Publication No. CA003031EN Article number 304263-MK August 2021 Changes to the products, to the information contained in this document, and to prices are reserved; as are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.







