

SIMATIC S7, MODBUS Master V3.1 single license for 1 installation R-SW, SW and DOCU on CD, HW dongle, Class A, 3 languages (de, de, fr, en fr), executable in STEP 7 V4.02 or higher, reference hardware: CP 341 and CP 441-2



Figure similar

Standards, approvals, certificates	
developed in accordance with IEC 61131	Yes
Operating systems	
Runs under operating system	
<ul style="list-style-type: none"> Windows 9x Windows ME Windows NT 4.0 Windows 2000 Windows XP Windows 7 	<ul style="list-style-type: none"> No No No No Yes Yes
Software	
Software class	A
Target system	SIMATIC CP 341/CP 441-2
Adjustable parameters	
<ul style="list-style-type: none"> Response monitoring time Factor for the character delay time Modem operation (ignore filler characters) RS 485 operation for 2-wire connection Preassignment of receive circuit on application of the X.27 interface module 	<ul style="list-style-type: none"> 100 ms to 25.5 s in 100-ms grid 1 or 10 with/without with/without Yes
Communication data	
<ul style="list-style-type: none"> CRC polynomial Receive mailbox Modbus protocol implemented function codes Broadcast Message Transmission rate V.24 control and signal cables Character delay time 	<ul style="list-style-type: none"> $X^{16} + x^{15} + x^2 + 1$ Specified on BRCV with RTU format 01, 02, 03, 04, 05, 06, 07, 08, 11, 12, 15, 16 possible 300 bit/s to 76 800 bit/s; (TTY to 19 200 bit/s) none 3.5 characters or multiples
Authorization/licenses	
<ul style="list-style-type: none"> Single license (EL) 	Yes
Documentation	
Languages	
<ul style="list-style-type: none"> German English French 	<ul style="list-style-type: none"> Yes Yes Yes

last modified:

3/4/2021