

Microwave detectors - Ceiling-mounted and tilt adjustable Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2) 1-10 DIM 0041581



Product features

Adjustable/tiltable ceiling recessed microwave presence/absence detector. 1-10V Direct dimming for controlling up to 10 luminaires. Lux level sensing. Time delay function. Infrared override. Dual senitivity offers configurable ON and OFF motion sensitivity. Programmable using programming handsets. Wide range of accessories including surface mounting backboxes and wall mounting bracket. Maintained illuminance capabillities. Scene setting and recall using user handset. Lamp burn in feature. IP40. Region 2 configuration = Rest of Europe excluding UK, France, Portugal, Germany, Switzerland, Austria, Slovakia, Ireland.

PRODUCT OVERVIEW

Product name	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2) 1-10 DIM
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000533
IP rating	IP40
Product EAN number	5410288415819
Max load (A)	10
Input	Microwave, Lux, IR
Input protocol	Microwave sensor
Output protocol	0-10V
Number of channels	2

DATA TABLE

General data	
Product name	Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2) 1-10 DIM
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Operating temperature range (°C)	-10°C - 50°C
ETIM Class	EC000533
Electrical data	
Mains voltage (V)	220-240V
Mains frequency (Hz)	50
Physical data	
IP rating	IP40



Microwave detectors - Ceiling-mounted and tilt adjustable Ceiling mounted Adjustable MW detector - lux sensing & time delay (Z2) 1-10 DIM 0041581

Nominal Product Length (mm)	85
Nominal Product Width (mm)	85
Nominal Product Height (mm)	92
Cutout Dimensions (W x L in mm or Diameter in mm)	74
Weight (kg)	0.155
Recessed Depth (mm)	92
Deckering	
Packaging	
Single packaging type	Carton
Product EAN number	5410288415819
Packaging single length / height (cm)	10.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	10.0
Units per outer package	96
Packaging outer length / height (cm)	63.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	47.0
Safety data	
Optimal operating condition (°C)	-10-50

TECHNICAL DRAWINGS

