

Ascent 100 II Arch 120 IP65


ASCENT 100 II ARCH 630 4K IP65 DALI EMG 120

2060689



Product features

- The ASCENT 100 II ARCH 630 4K DALI EMG 120 is a high efficient DALI dimmable downlight luminaire with 3 hour emergency, Colour rendering index Ra >80, Colour temperature: 4000K Neutral White, Class II, Protection rating IP65/IK02, Cut out dimensions: 137mm



PRODUCT OVERVIEW

Product name	ASCENT 100 II ARCH 630 4K IP65 DALI EMG 120
Technology	LED
Cap/Base	Cable
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	630
Luminous flux (lm)	630
Luminaire efficacy (lm/W)	90
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	85
Glare control	< 21
Photobiological Risk Group	RG0
Total power consumption (W)	7
Electrical protection	Class II
Control gear type	Electronic ballast
Control gear mounting	Remote
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK02
Product EAN number	5025768606894
Dimming method	DALI, Switch-dim (mains-rated)

Ascent 100 II Arch 120 IP65

ASCENT 100 II ARCH 630 4K IP65 DALI EMG 120
2060689

DATA TABLE

General data

Product name	ASCENT 100 II ARCH 630 4K IP65 DALI EMG 120
Technology	LED
Cap/Base	Cable
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
Operating temperature range (°C)	0°C - 25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

Optical data

Fixture luminous flux (lm)	630
Luminous flux (lm)	630
Luminaire efficacy (lm/W)	90
LOR (%)	100
Colour temperature (K)	4000
Correlated colour temperature range (K)	4000 - 4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	85
Glare control	< 21
Photobiological Risk Group	RG0
Emergency duration (h)	3

Electrical data

Total power consumption (W)	7
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class II
Control gear required	Yes
Control gear type	Electronic ballast
Control gear mounting	Remote
Transformer required	No
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	100
Drive current - Range (mA)	100mA / 100mA
Inrush Current (A)	5
Inrush Duration (µs)	20
Glow Wire Test (°C)	650

Ascent 100 II Arch 120 IP65

ASCENT 100 II ARCH 630 4K IP65 DALI EMG 120
2060689

Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 16A C Breaker	80
Max. Luminaires per 10A B Breaker	82
Max. Luminaires per 16A B Breaker	130

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	87500
Lifespan L90 B10	39500

Physical data


Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK02
Diffuser finish	Transparent
Diffuser material	Glass
Reflector finish	High-gloss
Nominal Product Height (mm)	94
Nominal Product Diameter (mm)	120
Cutout Dimensions (W x L in mm or Diameter in mm)	137
Weight (kg)	1.43

Packaging

Single packaging type	Carton
Product EAN number	5025768606894
Packaging single length / height (cm)	30.0
Packaging single width (cm)	30.0
Packaging single depth (cm)	12.5
DUN14 (outer)	05025768606894
Units per outer package	1
Packaging outer length / height (cm)	30.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	12.5

PHOTOMETRY

Ascent 100 II Arch 120 IP65 ASCENT 100 II ARCH 630 4K IP65 DALI EMG 120 2060689



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	1.05	93.0°	1178
1.0	2.11	46.5°	294
1.5	3.16	31.0°	131
2.0	4.22	23.2°	74
2.5	5.27	18.5°	47
3.0	6.32	15.8°	33

TECHNICAL DRAWINGS

