

Product Environmental Profile

ComPacT NSX630F 36 kA AC 3P 630A






General information

Representative product	ComPacT NSX630F 36 kA AC 3P 630A - C63F32D630
Description of the product	The main purpose of the Compact NSX AC C2 Plus is to protect and control low-voltage distribution systems, it follows IEC60947-1/IEC60947-2 and lifetime is 20 years
Functional unit	<p>Protect during 20 years the installation against overloads and short-circuits in circuit with assigned voltage 690 V AC and rated current 630A at 40°C.</p> <p>This protection is ensured in accordance with the following parameters:</p> <ul style="list-style-type: none"> - Number of poles 3 - Rated breaking capacity 40kA - Tripping curve long time, short time and instantaneous protections



Constituent materials

Reference product mass	6200 g including the product, its packaging and additional elements and accessories
-------------------------------	---



Plastics	20.5%
Metals	55.1%
Others	24.4%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information

The ComPacT NSX630F 36 kA AC 3P 630A presents the following relevant environmental aspects

Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 311.1 g, consisting of cardboard (86.8%), Plastics (6.5%), paper (6.7%) Product distribution optimised by setting up local distribution centres
Installation	Ref C63F32D630 does not require any installation operations
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic card (21.4g), Plastic parts with brominated FR17(8.467g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 53% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).




Environmental impacts

Reference life time	20 years			
Product category	Circuit-breakers			
Installation elements	No special components needed			
Use scenario	Load rate: 50% of In Use time rate: 30% of RLT			
Geographical representativeness	China			
Technological representativeness	The main purpose of the Compact NSX AC C2 Plus is to protect and control low-voltage distribution systems, it follows IEC60947-1/IEC60947-2 and lifetime is 20 years			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN

Compulsory indicators		ComPacT NSX630F 36 kA AC 3P 630A - C63F32D630					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2.74E-02	2.74E-02	0*	0*	6.99E-06	0*
Contribution to the soil and water acidification	kg SO ₂ eq	1.81E+00	7.56E-02	3.65E-03	0*	1.73E+00	1.75E-03
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	4.79E-01	2.26E-02	8.41E-04	0*	4.55E-01	4.89E-04
Contribution to global warming	kg CO ₂ eq	1.63E+03	3.77E+01	8.00E-01	0*	1.59E+03	9.26E-01
Contribution to ozone layer depletion	kg CFC11 eq	1.90E-04	1.77E-04	0*	0*	1.27E-05	4.02E-08
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2.13E-01	8.56E-03	2.61E-04	0*	2.04E-01	1.83E-04
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	2.26E+00	4.78E-01	0*	0*	1.78E+00	7.99E-04
Total Primary Energy	MJ	2.65E+04	4.72E+02	1.13E+01	0*	2.60E+04	8.53E+00

ENVPEP2106017_V1 - Product Environmental Profile - ComPacT NSX630F 36 kA AC 3P 630A



Optional indicators		ComPacT NSX630F 36 kA AC 3P 630A - C63F32D630						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to fossil resources depletion	MJ	2.43E+04	2.76E+02	1.12E+01	0*	2.41E+04	6.85E+00	
Contribution to air pollution	m³	1.78E+05	1.30E+04	3.40E+01	0*	1.65E+05	6.16E+01	
Contribution to water pollution	m³	8.51E+04	5.72E+03	1.32E+02	0*	7.92E+04	7.43E+01	
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Use of secondary material	kg	3.68E-01	3.68E-01	0*	0*	0*	0*	
Total use of renewable primary energy resources	MJ	1.35E+03	1.60E+01	0*	0*	1.34E+03	0*	
Total use of non-renewable primary energy resources	MJ	2.52E+04	4.56E+02	1.13E+01	0*	2.47E+04	8.52E+00	
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.35E+03	1.01E+01	0*	0*	1.34E+03	0*	
Use of renewable primary energy resources used as raw material	MJ	5.95E+00	5.95E+00	0*	0*	0*	0*	
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2.51E+04	4.04E+02	1.13E+01	0*	2.47E+04	8.52E+00	
Use of non renewable primary energy resources used as raw material	MJ	5.23E+01	5.23E+01	0*	0*	0*	0*	
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Hazardous waste disposed	kg	4.40E+02	3.80E+02	0*	0*	5.13E+01	8.58E+00	
Non hazardous waste disposed	kg	3.10E+02	2.11E+01	0*	0*	2.89E+02	0*	
Radioactive waste disposed	kg	1.84E-02	8.81E-03	2.02E-05	0*	9.51E-03	4.14E-05	
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Materials for recycling	kg	3.94E+00	5.93E-01	0*	2.90E-01	0*	3.05E+00	
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	
Materials for energy recovery	kg	1.25E-01	0*	0*	0*	0*	1.25E-01	
Exported Energy	MJ	9.01E-04	8.80E-05	0*	8.13E-04	0*	0*	

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.9.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

<i>Registration number</i>	ENVPEP2106017_V1	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Date of issue</i>	06/2021	<i>Supplemented by</i>	PSR-0005-ed2-EN-2016 03 29
<i>Validity period</i>	5 years	<i>Information and reference documents</i>	www.pep-ecopassport.org
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS
 Country Customer Care Center
<http://www.schneider-electric.com/contact>
 35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

ENVPEP2106017_V1

© 2019 - Schneider Electric – All rights reserved

06/2021