## **SIEMENS**

## **Data sheet**

## 3SU1853-3AA00-0AA1

Two-hand operation console for command devices, 22 mm, round, Enclosure material metal, enclosure top part gray, 3 control points, without equipment, with cable cut-outs for metric screw connections



product brand name	SIRIUS ACT	
product designation	Two-hand operation console	
product designation product type designation	3SU1	
Enclosure		
design of the housing	Two-hand operating console without standard equipment	
material of the enclosure	metal	
number of command points	3	
color of the enclosure top part	grey	
delivery state	gicy	
• as a kit	No	
pre-wired on strip terminal	No	
fastening method of the enclosure	Horizontal	
Actuator	Horizontal	
	Unaquinned	
design of the actuating element principle of operation of the actuating element	Unequipped without	
product feature	Without	
lockout	No	
	No	
<ul> <li>staggered switching</li> <li>number of contact modules</li> </ul>	0	
General technical data		
product function	No	
positive opening     FMEDGENCY OFF function	No	
EMERGENCY OFF function     EMERGENCY STOP function	No No	
EMERGENCY STOP function  And the description  The description of	No	
product component stand/pedestal	No	
protection class IP	IP66	
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13	
shock resistance according to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms	
vibration resistance according to IEC 60068-2-6	10 500 Hz: 5g	
reference code according to IEC 81346-2	U	
Substance Prohibitance (Date)	10/01/2014	
Auxiliary circuit		
number of NC contacts for auxiliary contacts	0	
number of NO contacts for auxiliary contacts	0	
	Connections/ Terminals	
type of electrical connection on enclosure	Cable routing at the rear 2 x M25	
Ambient conditions		
ambient temperature		
<ul><li>during operation</li></ul>	-25 +70 °C	
<ul> <li>during storage</li> </ul>	-40 +80 °C	
environmental category during operation according to IEC	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%, no	

60721	condensation in operation permitted for all devices behind front panel)	
Installation/ mounting/ dimensions		
height	185.6 mm	
width	492.4 mm	
depth	159.5 mm	
Accessories		
number of backing plates	0	
Certificates/ approvals		
General Product Approval	Declaration of Conformity	

Confirmation











**Test Certificates** 

Marine / Shipping

Special Test Certificate

Type Test Certificates/Test Report









Marine / Shipping

other



Environmental Confirmations Confirmation

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1853-3AA00-0AA1


Cax online generator


http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1853-3AA00-0AA1


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1853-3AA00-0AA1

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax">http://www.automation.siemens.com/bilddb/cax</a> de.aspx?mlfb=3SU1853-3AA00-0AA1&lang=en







last modified:

1/26/2022