# **SIEMENS**

## **Data sheet**

## 6GK5795-6MP00-0AA0

### product type designation



#### Antenna ANT795-6MP

ANT795-6MP IWLAN antenna with omnidirectional characteristic; incl. N-Female plug: 5/7 dBi; IP65/67 (-40-+80 °C); 2.4/5 GHz Wi-Fi compliance and observe national approvals; mounting on wall or mast; compact instructions on German/English scope of delivery: 1x ANT795-6MP, 1x mounting aid.

## radio frequencies

type of wireless network / is supported operating frequency

- for WLAN in 2.4 GHz frequency band
- for WLAN in 5 GHz frequency band 1

antenna gain compared to spherical radiator

- of the WLAN antenna / in the 2.4 GHz frequency band
- of the WLAN antenna / in the 5 GHz frequency band

#### **WLAN**

2.4 ... 2.5 GHz 4.94 ... 5.925 GHz

5 dB

7 dB

## electrical data

impedance polarization

radiation characteristic

antenna gain compared to spherical radiator

- of the WLAN antenna / in the 2.4 GHz frequency band
- of the WLAN antenna / in the 5 GHz frequency band standing wave ratio (VSWR) / maximum radiating angle of the antenna
  - in the 2.4 GHz frequency band / horizontal
  - in the 2.4 GHz frequency band / vertical
  - in the 5 GHz frequency band / horizontal
  - in the 5 GHz frequency band / vertical

number of electrical connections / of the antenna type of electrical connection / of the antenna

angle of inclination / downward / maximum

#### o ub

50 Ω linear vertical omnidirectional

5 dB

7 dB

2

360° 25°

360°

15°; take the antenna diagram into account regarding the horizontal beam angle

1

N-Connector female 0°

#### mechanical data

material

of outer shell

design of plug-in connection

## UV-resistant white plastic

#### ambient conditions

ambient temperature

- during operation
- during storage
- during transport

protection class IP wind load / maximum

resistance to salt-laden atmosphere / conformity according to EN 60068-2-52

-40 ... +80 °C

-40 ... +80 °C

-40 ... +80 °C

IP65/67 19.6 N

Yes; Severity 1

design, dimensions and weights	
width	97 mm
height	367 mm; incl. bracket
depth	64 mm
diameter	28.6 mm
net weight	140 g
fastening method	
<ul><li>mast mounting</li></ul>	Yes
<ul><li>wall mounting</li></ul>	Yes
<ul><li>roof mounting</li></ul>	No
<ul> <li>directly on the device</li> </ul>	No
product features, product functions, product components / general	
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	
<ul> <li>RoHS conformity</li> </ul>	Yes
product conformity	UL 94-HB
wireless approval	Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen
reference code / according to IEC 81346-2:2019	TFB
further information / internet-Links	
Internet-Link	
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 5/11/2022 🖸