

AS-Interface accessory IP68 T-distributor U\_ASi and Uaux for round cable 1 x M12 connector, 2 x M12 socket



General technical data			
Type of device		AS-Interface accessories	
design of the product		M12-T distribution board	
Function		T distribution M12	
Connections/ Terminals			
type of electrical connection		M12	
AS interface			
• Connection		1 x M12 connector / 2 x M12 box	
Inputs			
Inputs socket assignment		1 = AS-i "+" 2 = Uaux "-" 3=AS-i "-" 4 = Uaux "+"	
Mechanical data			
Type of mounting		screw fixing	
Contacts Load rating max	A	4	
Ambient conditions			
ambient temperature	°C	-25 ... +85	
ambient temperature during storage	°C	-25 ... +85	
degree of protection		IP68	
Certificates/ approvals			
General Product Approval	EMC	Declaration of Conformity	Marine / Shipping

[Confirmation](#)



EG-Konf.



ABS



PRS

Marine / Shipping other



RMRS

[Confirmation](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RK1901-1TR00>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-1TR00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-1TR00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RK1901-1TR00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-1TR00&lang=en)

last modified:

1/18/2021 