

product type designation



MDS D324 transponder

Transponder MDS D324 for RF200/RF300 ISO/MOBY D button ISO 15693, Chip type INFINEON SRF 55V10P, 992-byte user memory; 27x 4 mm (DxH); Minimum order quantity 20 units.

suitability for operation

RF200, RF300, MOBY D

radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	280 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	ISO 15693
transfer rate / with radio transmission / maximum	26.5 kbit/s
product feature / multitag-capable	Yes

electrical data

product component / backup battery	No
------------------------------------	----

memory

type of memory	EEPROM
storage capacity / of the user memory	992 byte
type of memory organization	UID (fixed code) 8 bytes, user memory 992 bytes, configuration memory 24 bytes
number of read cycles / at ambient temperature < 40 °C / maximum	1000000000000000
number of write cycles / at ambient temperature < 40 °C / maximum	1000000
data retention time / at ambient temperature < 40 °C / not less than	10 y
property of memory	Block-by-block write protection of the user memory
type of transponder chip used	Infineon My-D SRF 55V10P

mechanical data

material	Epoxy resin
color	black
tightening torque / of the screw for securing the equipment / maximum	1 N·m
mounting distance / relating to metal surfaces / recommended / minimum	15 mm

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during read/write access outside the read/write area during storage 	-25 ... +125 °C -40 ... +140 °C -40 ... +140 °C
protection class IP	IP67
shock resistance	According to DIN EN 60721-3-7 Class 7 M3
shock acceleration	1000 m/s ²
vibrational acceleration	200 m/s ²

design, dimensions and weights

height	4 mm
--------	------

diameter	27 mm
net weight	5 g
fastening method	M3 screw, gluing
product features, product functions, product components / general	
product feature	
• silicon-free	Yes
• printable	No
standards, specifications, approvals	
certificate of suitability	
• IECEx	No
MTBF	171 y
accessories	
accessories	Mounting support and spacer
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	12/18/2020 