



SIMATIC ET 200SP, BusAdapter BA SCRJ/RJ45, media converter FOC-CU 1x SCRJ FO connection and, 1x RJ45 connection

General information	
Product type designation	BA SCRJ/RJ45
HW functional status	from FS04
Interfaces	
Number of PROFINET interfaces	1; 2 ports (SCRJ + RJ45)
Supports protocol for PROFINET IO	
<ul style="list-style-type: none"> <li>Number of RJ45 ports</li> <li>Number of SCRJ ports</li> <li>Number of LC ports</li> </ul>	1 1 0
Cable length	
— PCF	100 m
— Plastic FOC (POF)	50 m
— PCF-GI	250 m
— Cu conductors	100 m
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-25 °C 60 °C -25 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual
Dimensions	
Width	20 mm
Weights	
Weight, approx.	50 g
last modified:	3/14/2022