

## Pneumatic contact fem. with valve 3,0 mm



|                    |   |
|--------------------|---|
| Part number        | 09 14 000 6257  |
| Specification      | Pneumatic contact fem. with valve 3,0 mm  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09140006257">https://b2b.harting.com/09140006257</a> |

### Identification

|                            |  |
|----------------------------|--|
| Category                   | Contacts                               |
| Type of contact            | Pneumatic contact                      |
| Description of the contact | With shut-off Polypropylen<br>Straight |

### Version

|        |        |
|--------|--------|
| Gender | Female |
|--------|--------|

### Technical characteristics

|                      |                |
|----------------------|----------------|
| Limiting temperature | -40 ... +80 °C |
| Operating pressure   | ≤8 bar         |
| Tube inner diameter  | 3 mm           |

### Material properties

|                             |               |
|-----------------------------|---------------|
| Material (contacts)         | Delrin acetal |
| Material (seal)             | Buna-N        |
| RoHS                        | compliant     |
| ELV status                  | compliant     |
| China RoHS                  | e             |
| REACH Annex XVII substances | No            |
| REACH ANNEX XIV substances  | No            |
| REACH SVHC substances       | No            |



Pushing Performance

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 10   |
| Net weight                     | 0.64 g                                     |
| Country of origin              | Germany                                    |
| European customs tariff number | 39269097                                   |
| eCl@ss                         | 27440204 Contact for industrial connectors |