


# BS-400A Four Pole Insulating Support – BS-400A (551250)



- Create custom four pole distribution blocks for an electrical distribution system
- Protection screen can be attached directly to the support
- Includes screws to mount threaded copper busbars
- Easily clips onto DIN rail or mounts to panel with screws
- Halogen free
- RoHS compliant



Part Number	BS-400A
Article Number	551250
Material	Steel Glass Fibre Reinforced Polyamide
Finish	Electrogalvanized
Max Working Voltage, IEC (Ui)	1.000 VAC 1.500 VDC
Working Temperature	-40 to 130 °C
Typical Application Current Rating	160 – 630 A
Complies With	IEC® 60439.1 IEC® 61439.1 IEC® 60695-2-11 (Glow Wire Test 960 °C)
Flammability Rating	UL® 94V-0
Busbar Width	15 – 32 mm
Busbar Thickness	5 – 10 mm
Depth [D]	128 mm
Height [H]	230 mm
Width [W]	34 mm
A	123 mm
Screw Diameter [Sc]	M6
Unit Weight	0,22 kg
Certifications	CE EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports RoHS

Part Number	BS-400A
Standard Packaging Quantity	2 pc
UPC	78285686015
EAN-13	3479775512501

Must be used with copper busbars.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.