



Representative Image

## Ref. No. 666581 | Cat. No. ASTR4040

**Description:** ASTER rotary switch 40A 4NO 415Vac

**EAN** 5413656665816

**Home > Modular DIN-rail devices > Comfort functions > Switches, Push Buttons and Indicator Lamps**

**Description:**

• **Function:**

Manual control of all kinds of electrical devices.

• **Applications:**

Switching of lighting and heating in homes, shops, offices, warehouses, factories, hospitals, etc.

• **Features:**

Wide range with respect to available contact combinations and switching capacity. Mainbs disconnect switches with change-over contact and off position available.

Compact (4pole in 1 module) wtih high switching capacity due to double interruption per path.

All switches are sealable through padlock or by means of a lock.

The terminals are equipped with captive Pozidriv screws and have IP20 protection degree.

Main disconnect switches accepts auxiliary contacts CA.

### Descriptors

Category	Switches, Push Buttons and Indicator Lamps
----------	--

### Specifications

Series	Rotary switch
Nominal current In	40A/415Vac
Number of modules	4
Contact combination	4NO
Standards	NBN EN 60947-3, EN 60947-3
Switching possibilty (V)	40A/415V
Protection Degree	IP20
Screws	Pozidriv 2
Usable as mains disconnect switch	Yes
Short-circuit resistance without upfront fuses	10kA (summit)
Short-circuit resistance with upfront fuses	15kA (nom)
Nominal breaking capacity at 415Vac, cos (phi) = 0,95	1.5 xIn
Mechanical service life (complete on-off-cycle)	>10000
Electrical service life, cos j = 0,95, Un and In	>1500
Nominal breaking capacity at 415Vac, cos (phi) = 0,65	3xInom
Nominal voltage multipole devices	240/415Vac
Terminal capacity max (mm <sup>2</sup> )	1 x 25 mm <sup>2</sup>
Terminal capacity min (mm <sup>2</sup> )	1 x 2.5 mm <sup>2</sup>

### Classifications

Approvals	VDE, CEPEC, KEMA, CE
ETIM 5.0	EC000216 - Switch disconnecter

**by ABB**

### Classifications

ETIM 6.0	EC000216 - Switch disconnecter
----------	--------------------------------

### Dimensions

Weight	0.310 kg
--------	----------

### Package Information

Standard packing	1
------------------	---