

Completely pre-assembled Signal Towers / KOMPAKT 37

K37cl sr cable EM 12VAC/DC GN/RD



Part No.:	698.320.74
Series:	Kompakt 37



MECHANICAL DATA

Height	141 mm
Diameter	38 mm
Materials	PC
Dome colour	Clear
Housing colour	Black
Protection category	IP65
Connection	Cable
cross-sectional area maximum	0,34mm ² / 22AWG
Cable entry	Membrane grommet
Cable entry minimum	d = 1 mm
Cable entry maximum	d = 9 mm
Cable length	2000 mm
Tension relief	Pull-out protection
Type of fixing	Built-in mounting
Service life optical	50,000 h maximum
Working temperature minimum	-20°C
Working temperature maximum	+50°C
UL Type Rating	Type 12 Type 4X
Weight with packaging	80 g
Product weight	80 g

ELECTRICAL DATA

Operating voltage	12V
Operating voltage type	AC/DC
Operating voltage type	50Hz
Operating voltage tolerance	+/- 10%
Rated operational voltage	12 VDC
Rated operational current	175 mA
Rated inrush current	500 mA
Protection class	Protection class 2
Pollution degree	3 In the connection area: 2

OPTICAL DATA

Light source	LED
Light colour	Green Red
Optical signal image	Permanent



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

K37cl sr cable EM 12VAC/DC GN/RD

Technical drawing of the 698/699 series pressure washer lance, showing five different sizes. The drawing includes dimensions for the lance diameter ($\varnothing 37,5$), the trigger gun diameter ($\varnothing 27,7$), and the total length of the lance (229,5 mm). The lance is divided into sections of 34 mm and 12,8 mm. The trigger gun has a length of 93,5 mm. The lance is shown in five different sizes, with the total length of the lance decreasing from 229,5 mm to 161,5 mm. The trigger gun is shown in five different sizes, with the total length of the trigger gun decreasing from 93,5 mm to 8,5 mm. The trigger gun is shown in five different sizes, with the total length of the trigger gun decreasing from 93,5 mm to 8,5 mm. The trigger gun is shown in five different sizes, with the total length of the trigger gun decreasing from 93,5 mm to 8,5 mm.

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.