

Declaration of Performance (DoP) (

Nr. DoP0003

- 1. Unique identification code for the product type: See appendix 1 (page 2/2)
- Intended use of the construction product:
 Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke.
- 3. Manufacturer:
 TKF (B.V. Twentsche Kabelfabriek)
 Spinnerstraat 15
 7481 KJ Haaksbergen
 Netherlands

Tel.: +31(0)53 573 22 55 E-mail: info@tkf.eu www.tkf.eu

- 4. System of assessment and verification of constancy of performance of the construction product asset out in CPR. Annex V: **System 3**
- 5. Notified body: **NB 0402**
- 6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification	
Reaction to fire	Dca-s3, d2, a3	EN50575:2014	
Dangerous substances	NPD	(EC) No 1907/2006 (REACH)	

7. The performance of the product identified is in conformity with the declared performance.

This declaration of performance is issued. in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer indentified in this document.

Signed for and on behalf of B.V. Twentsche Kabelfabriek by:

Managing Director

Haaksbergen, January 06, 2020



TKF CONNECTIVITY SOLUTIONS

CE

Nr. DoP0003

Appendix 1

Product type	Number of cores	Conductor cross-section [mm²]		
YMvK Dca 0.6/1 kV	1	10 to 240		
YMvK Dca 0.6/1 kV	2 to 5	1.5 to 185		
YMvK Dca 0.6/1 kV	6 to 37	1.5 to 2.5		
VO-YMvKas Dca 0.6/1 kV	2 to 5	1.5 to 10		
VO-YMvKas Dca 0.6/1 kV	6 to 37	1.5		
VO-YMvKas Dca 0.6/1 kV	6 to 52	2.5		
VO-YMvKas Dca 0.6/1 kV	6	6		
VO-YMvKas Dca 0.6/1 kV	30	4		
VG-YMvKas Dca 0.6/1 kV	1	25 to 630		
VG-YMvKas Dca 0.6/1 kV	2 to 5	10 to 120		
VG-YMvKas Dca 0.6/1 kV	3 to 4	120 to 300		
Instalflex YMvK-ss Dca 0.6/1 kV	1	25 to 630		
Instalflex YMvK-ss Dca 0.6/1 kV	4 to 5	10 to 300		

Product type	Number of cores	Conductor cross- section [mm²]	Number of auxiliary cores	Conductor cross- section [mm²] auxiliary cores
VO-YMvKhas Dca 0.6/1 kV	4	10	4	2.5
VO-YMvKhas Dca 0.6/1 kV	4	16	4	2.5
VG-YMvKhas Dca 0,6/1kV	4	25	4	2,5