



Product data sheet


Item No. 92.932.3053.1

Male connector with strain relief GST18I3S S1 ZR1 SW

Connector GST18i3, 3 pole, male, screw connection, 250 V, 20 A, colour of coding: black, colour of housing: black



Item No.	92.932.3053.1
EAN	4015573721876
Order Unit	50 Piece(s)





Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	10.5 mm
Cable diameter 2	6.5 mm
Connection cross section solid	2.5 mm ²
Cross section solid 2	0.75 mm²
Connection cross section stranded	2.5 mm ²
Cross section stranded 2	0.75 mm ²

💎 wieland



Terminations per pole	1		
Model			
Model	male		
Number of poles	3		
Connection type	Screw connection		
Degree of protection (IP)	IP40		
Material			
Housing material	Polyamide		
Halogen free	Yes		
Contact material	CuZn		
Insulation components continous temperature	100 °C		
Surface finish	Tin-plated		

Dimensions

Length	69.4 mm
Width	28.2 mm
Height	12.6 mm

Technical drawing

