

START Downlight Flat Dimmable 226mm Round Surface

START eco Downlight Flat 226 1700lm 830 DIM Surface

0053946



Product features

- START eco Downlight Flat DIM Surface is an integrated LED surface mounted downlight with a separate, phase dimmable driver and loop in- out box, 17W; 1700Lm; 100Lm/W; 3000K; IP20.



PRODUCT OVERVIEW


Product name	START eco Downlight Flat 226 1700lm 830 DIM Surface
Technology	LED
Housing	Aluminium
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278201
Warranty	3 years
Fixture luminous flux (lm)	1700
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK06
Product EAN number	5410288539461

PHOTOMETRY

START Downlight Flat Dimmable 226mm Round Surface

START eco Downlight Flat 226 1700lm 830 DIM Surface

0053946



Distance [m]	Cone diameter [m]	E0° [lx]	E10° [lx]	E30° [lx]	E45° [lx]	E60° [lx]	E75° [lx]	E90° [lx]
0.5	1.44	292	221	100	56	35	23	14
	1.62	221	166	78	44	28	18	11
1.0	2.25	155	117	54	31	19	12	8
	2.56	117	90	44	24	15	9	6
1.5	3.24	100	76	37	20	12	7	5
	3.61	76	58	28	15	9	5	3
2.0	4.00	78	59	29	16	10	6	4
	4.41	59	45	22	12	7	4	3
2.5	4.96	67	51	24	13	8	5	3
	5.44	51	39	19	10	6	4	3
3.0	5.67	66	50	24	13	8	5	3
	6.37	50	38	18	10	6	4	3

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 110.0°) — C90 - C270 (Half beam angle: 110.0°)

TECHNICAL DRAWINGS

