



#### Product features

- LED retrofit replacement for halogen G9 mains voltage capsules
- ToLEDo Retro G9 has the same look and feel as halogen design thanks to glass construction body and wide light distribution
- Compact design
- Omni-directional light distribution
- 250lm = 25W halogen G9 lamp
- 90% energy saving
- Non-dimmable
- Suitable for chandeliers, interior display, shop windows, decorative and general lighting applications



### **PRODUCT OVERVIEW**

Product name	ToLEDo Retro G9 CL 250LM 827 SL2
Technology	LED
Watt (Rated) (W)	2.2
Туре	LED exchangeable
Cap/Base	G9
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Warranty	3 years
Luminous flux (Im)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Wattage (W)	2.2
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	12000
Product EAN number	5410288296654




# DATA TABLE

General data	
Product name	ToLEDo Retro G9 CL 250LM 827 SL2
Technology	LED
Watt (Rated) (W)	2.2
Туре	LED exchangeable
Cap/Base	G9
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	3 years
Optical data	
Luminous flux (Im)	250
Luminous flux (Rated) (Im)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%) Electrical data	70
Wattage (W)	2.2
Equivalent watt (W)	25
Product Voltage (V)	230
Control gear required	No
No. Of switching cycles before premature	>50000
failures	
Transformer required	No
Dimmable	No
Inrush Current (A)	1.2
Inrush Duration (µs)	520
	520
Lamp Energy Label (class)	520 E
Lamp Energy Label (class) Nominal Frequency (Hz) Max. Luminaires per 16A C Breaker	E
Lamp Energy Label (class) Nominal Frequency (Hz)	E 50/60Hz
Lamp Energy Label (class) Nominal Frequency (Hz) Max. Luminaires per 16A C Breaker	E 50/60Hz 133
Lamp Energy Label (class) Nominal Frequency (Hz) Max. Luminaires per 16A C Breaker Max. Luminaires per 16A B Breaker Lifetime data	E 50/60Hz 133 66
Lamp Energy Label (class) Nominal Frequency (Hz) Max. Luminaires per 16A C Breaker Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50	E 50/60Hz 133 66 15000
Lamp Energy Label (class) Nominal Frequency (Hz) Max. Luminaires per 16A C Breaker Max. Luminaires per 16A B Breaker Lifetime data	E 50/60Hz 133 66



Physical data	
Nominal Product Length (mm)	52.5
Nominal Product Diameter (mm)	15
Weight (kg)	0.016
Packaging	
Single packaging type	Carton
Product EAN number	5410288296654
Packaging single length / height (cm)	6.1
Packaging single width (cm)	5.1
Packaging single depth (cm)	8.2
DUN14 (outer)	15410288296651
Units per outer package	6
Packaging outer length / height (cm)	19.1
Packaging outer width (cm)	11.0
Packaging outer depth (cm)	9.5
Safety data	
Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

# PHOTOMETRY



# **TECHNICAL DRAWINGS**

