

OptiClip 600x600

OptiClip 600 3000K C8 HO WH DALI WHITE

0043005



Product features

- OPTICLIP 600 3000K C8 HO WH DALI WHITE is a high efficacy low glare luminaire with replaceable light engines for office and education applications. Ceiling recessed LED luminaire with white colour plastic optic, direct light distribution, luminaire dimensions: 595x595x20mm, Sylvania White body colour (RAL9016), IP40 (from the front), IK07, DALI Dimmable, low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 3925lm luminous flux, 33W power consumption, 119lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 2000 cd/m2, lifespan: 62,000 hours L80B20, photobiological safety risk group 1. Electrical protection Class II. Glow wire test 850°C.



PRODUCT OVERVIEW

Product name	OptiClip 600 3000K C8 HO WH DALI WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	3925
Luminaire efficacy (lm/W)	119
Colour temperature (K)	3000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	80
Glare control	< 17
Photobiological Risk Group	RG1
Total power consumption (W)	33
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Product EAN number	5410288430058


OptiClip 600x600 OptiClip 600 3000K C8 HO WH DALI WHITE 0043005

PHOTOMETRY

0.5	0.81 0.63	E(0°) 6471 E(C90) 28.9° 2232 E(C0) 18.8° 2142
1.0	1.61 1.07	E(0°) 2388 E(C90) 28.9° 588 E(C0) 18.8° 557
1.5	2.42 2.50	E(0°) 1548 E(C90) 18.9° 545 E(C0) 18.8° 235
2.0	3.23 3.33	E(0°) 988 E(C90) 28.9° 540 E(C0) 18.8° 174
2.5	4.03 4.17	E(0°) 577 E(C90) 28.9° 89 E(C0) 18.8° 86
3.0	4.84 5.00	E(0°) 382 E(C90) 28.9° 41 E(C0) 18.8° 39

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 79.8°)
— C90 - C270 (Half beam angle: 77.8°)



TECHNICAL DRAWINGS

