

START eco Panel 600x600

START eco Panel 600x600 3200Lm 830

0047669



Product features

- Back lit LED panel, Low Flicker, 36 W, Warm White, 3000 K, 3200 lumens, 89 lm/W, Average lifespan: 100.000Hrs, electronic non dimmable driver. (HxWxD) 34 x 595 x 595 mm.




PRODUCT OVERVIEW

Product name	START eco Panel 600x600 3200Lm 830
Technology	LED
Housing	Aluminium, Steel
Mount	Ceiling recessed mounting
Environment	Interior
General application	Education, Office
ETIM Class	EC002892
Warranty	3 years
Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	89
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	112
Glare control	< 22
Photobiological Risk Group	RG0
Total power consumption (W)	36
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP40/20
IK rating	IK02
Product EAN number	5410288476698

PHOTOMETRY

START eco Panel 600x600

START eco Panel 600x600 3200Lm 830
0047669



Distance [m]	Cone diameter [m]	E(0°) [lx]	E(C0) [lx]	E(112.0°) [lx]
0.5	1.45	5071	5071	4527
1.0	2.97	1267	1267	1130
1.5	4.45	539	539	482
2.0	5.93	312	312	281
2.5	7.41	197	197	177
3.0	8.90	121	121	111

Distance [m] Cone diameter [m]
E(0°) E(C0) E(112.0°) Illuminance [lx]
C0-C180 (Half beam angle: 112.0°)

TECHNICAL DRAWINGS

